

## OREO V Out



### Product characteristics

**Body**

Aluminium

**Finish**

Powder coated

**Optical system**

bLINE - Opal diffuser

**Light source**

LED, RG1, CRI>90, MacAdam Step  $\leq 3$

**LED lifetime**

60.000h @ L80, B10, Ta 25°C

**Control gear**

Not included




# 01. Select version




## OREOV Out

\*Replace the symbols to complete the code



### bLINE - Opal diffuser



W	lm output	lm/W	Dmm	CODE*
22	1238	56	Ø630	90419L6300▲0♦00
35	1966	56	Ø950	90419L9500▲0♦00
47	2694	57	Ø1270	90419L1270▲0♦00
59	3349	57	Ø1555	90419L1550▲0♦00
76	4295	57	Ø1970	90419L1970▲0♦00

## OREOV Out

- Current supply cable/suspension with 1500 mm included.
- To complete the product add ceiling rose. Please order separately.
- For Ø1555 and Ø1970 mm versions, the product must include a transparent power cable.
- For Tunable White and RGB White versions, the product must include a transparent current supply cable.

Colour <sup>1</sup>	Symbol
White	W
Grey	G
Black	B
Sahara	0
Mist	1
Carbon	I
Autumn	L
Rusty chain	R
Jungle	N
Golden eye	D
Old rose	5
Copper	7

Colour temp.	Symbol
2700K	2
3000K	3
4000K	0
Tunable White <sup>2</sup>	T
RGB White <sup>3</sup>	R

<sup>1</sup> See page 212.

<sup>2</sup> Tunable White (3000K - 5700K). Only available with ceiling rose TW + OmniaControl.

<sup>3</sup> RGB White (2700K). Only available with ceiling rose RGB White + OmniaControl.

## 02. Select ceiling rose



### Trimless

50 | | Ø120

Ø128

HF

	CODE*
Ø630	976700
Ø950, Ø1270	976701
Ø1555, Ø1970	976703

DALI

	CODE*
Ø630	976800
Ø950, Ø1270	976801
Ø1555, Ø1970	976803

OmniaControl

	CODE*
Ø630	976900
Ø950, Ø1270	976901
Ø1555, Ø1970	976903

RGB White + OmniaControl

	CODE*
Ø630, Ø950	976905
Ø1270, Ø1555	976907
Ø1970	976909

Tunable White + OmniaControl

	CODE*
Ø630, Ø950	976910
Ø1270, Ø1555	976912
Ø1970	976914

### Recessed

82 | | Ø150

Ø128

HF

	CODE*
Ø630	976400
Ø950, Ø1270	976401
Ø1555, Ø1970	976403

DALI

	CODE*
Ø630	976500
Ø950, Ø1270	976501
Ø1555, Ø1970	976503

OmniaControl

	CODE*
Ø630	976600
Ø950, Ø1270	976601
Ø1555, Ø1970	976603


RGB White + OmniaControl

	CODE*
Ø630, Ø950	976605
Ø1270, Ø1555	976607
Ø1970	976609

Tunable White + OmniaControl

	CODE*
Ø630, Ø950	976610
Ø1270, Ø1555	976612
Ø1970	976614

### Surface mounted



HF

	CODE*
Ø630 <sup>a)</sup>	976100
Ø950, Ø1270 <sup>a)</sup>	976101
Ø1555, Ø1970 <sup>b)</sup>	976103

DALI

	CODE*
Ø630 <sup>a)</sup>	976200
Ø950, Ø1270 <sup>a)</sup>	976201
Ø1555, Ø1970 <sup>b)</sup>	976203

OmniaControl

	CODE*
Ø630 <sup>a)</sup>	976300
Ø950, Ø1270 <sup>a)</sup>	976301
Ø1555, Ø1970 <sup>b)</sup>	976303

RGB White + OmniaControl

	CODE*
Ø630, Ø950 <sup>a)</sup>	976305
Ø1270 <sup>a)</sup>	976307
Ø1555 <sup>b)</sup>	976308
Ø1970 <sup>b)</sup>	976309

Tunable White + OmniaControl

	CODE*
Ø630, Ø950 <sup>a)</sup>	976310
Ø1270 <sup>a)</sup>	976312
Ø1555 <sup>b)</sup>	976313
Ø1970 <sup>b)</sup>	976314

\*Replace the symbols to complete the code

Colour	
<input type="checkbox"/> White	W
<input type="checkbox"/> Black	B

### CEILING ROSE

- Control gear included in the ceiling rose.
- The trimless recessed ceiling rose is class III.
- The surface ceiling rose is class I.

### Product details



bLINE diffuser




Clip-in diffuser



Trimless recessed ceiling rose



Recessed ceiling rose



Surface ceiling rose

