

REBA 30 SAPP Line



Product characteristics

Body

Extruded aluminium profile

Finish

Epoxy polyester powder coated

Optical system

LIGHT+ - Opal diffuser

bOPTICS - Symmetric reflector

Light source

LED, RG1, CRI>80, MacAdam Step ≤3

LED lifetime

80.000h @ L90, B10, Ta 25°C

Control gear

LED driver 220-240V-50/60Hz included



230V/50Hz



IP 20


650°C




01. Select version



REBA 30 SAPP Line




LIGHT+ - Opal diffuser



W	lm output	lm/W	Lmm	CODE*
11	1185	108	847	90954L003▼▲0♣
15	1579	105	1129	90954L004▼▲0♣
18	1973	110	1410	90954L005▼▲0♣
22	2368	108	1692	90954L006▼▲0♣
26	2763	106	1973	90954L007▼▲0♣

bOPTICS - Symmetric reflector



W	lm output	lm/W	Lmm	CODE*
12	1531	129	958	90955L003▼▲0♣
15	2041	136	1277	90955L004▼▲0♣
19	2552	134	1595	90955L005▼▲0♣
23	3062	133	1914	90955L006▼▲0♣
26	3572	137	2232	90955L007▼▲0♣

*Replace the symbols to complete the code

Control gear ▼

HF	E
DALI	H

Colour ▲

□ White	W
■ Grey	G
■ Black	B

Colour temp. ♦

3000K	3
4000K	0

Module ♣

SRT/MID	58
END	50

REBA 30 SAPP Line


• The values indicated refer to the colour white.




Product details



Application on SAPP ceilings



LIGHT+ diffuser



bOPTICS diffuser