

REBA 45 LITE



Product characteristics

Body

Extruded aluminium profile

Finish

Epoxy polyester powder coated

Optical system

bOPTICS - Symmetric reflector

Light source

LED, RG1, CRI>80, MacAdam Step ≤3

LED lifetime

80.000h @ L80, B10, Ta 25°C

Control gear

LED driver 220-240V-50/60Hz included



230V/50Hz




IP 40

650°C


01. Select version



REBA 45 LITE



bOPTICS - Symmetric reflector



W	lm output	lm/W	Lmm	CODE*
14	1910	136	566	90974L006▼▲0♦00
27	3819	141	1126	90974L012▼▲0♦00
34	4774	140	1406	90974L015▼▲0♦00
40	5729	143	1686	90974L017▼▲0♦00
68	9548	140	2806	90974L030▼▲0♦00

*Replace the symbols to complete the code

Control gear	▼
HF	E
DALI	H

Colour	▲
□ White	W
■ Black	B

Colour temp.	♦
3000K	3
4000K	0

REBA 45 LITE

• To complete the product, it is necessary to order the suspension and the power supply kit separately.

02. Select options

OPTIONS		Code*
Suspension		
S16 L1500 mm (x2)		913400
S16 L3000 mm (x2)		913401
S16 L6000 mm (x2)		913402
Power supply kit		
L1500mm - 3 x 0,75 mm ²	35 l  Ø85	943000♣
L1500mm - 5 x 0,75 mm ²		943003♣
L3000mm - 3 x 0,75 mm ²		943001♣
L3000mm - 5 x 0,75 mm ²		943004♣
L6000mm - 3 x 0,75 mm ²		943002♣
L6000mm - 5 x 0,75 mm ²		943005♣
• Ceiling rose and current supply cable included.		



*Replace the symbols to complete the code

Colour		♣
☐ White		W
☒ Black		B



Product details



Suspension



Ceiling rose

