

REBA 50



Product characteristics

Body

Extruded aluminium profile

Finish

Powder coated

Optical system

bGLARE - Microprismatic diffuser

bLINE - Opal diffuser

ASYM - Asymmetric diffuser

Light source

LED, RG1, CRI>80, MacAdam Step ≤3

LED lifetime

80.000h @ L90, B10, Ta 25°C


Control gear

LED driver 220-240V-50/60Hz included



01. Select Outer Profile

OUTER PROFILE



Lmm	CODE*
578	90517L0020
858	90517L0030
1138	90517L0040
1418	90517L0050
1698	90517L0060
1980	90517L0070
2260	90517L0080
2540	90517L0090
2820	90517L0100



*Replace the symbols to complete the code


Colour	
White	W
Grey	G
Black	B

OUTER PROFILE


- To complete the product add the inner profile. Please order separately.
- For suspended version add the suspension, current supply cable and ceiling rose. Please order separately.

02. Seleccionar perfil interior e Diffuser

INNER PROFILE | SYMMETRIC



bGLARE - Microprismatic diffuser




W	lm output	lm/W	Lmm	CODE*
15	1603	107	562	90498L002
22	2405	109	842	90498L003
30	3207	107	1122	90498L004
35	4008	115	1402	90498L005
42	4810	115	1682	90498L006
52	5612	108	1964	90498L007
60	6413	107	2244	90498L008
65	7215	111	2524	90498L009
70	8017	115	2804	90498L010


*Replace the symbols to complete the code

Control gear	
HF	E
DALI	H

Emergency	
No EM	0
EM 3h (K3) ^{1,2}	3




bLINE - Opal diffuser




W	lm output	lm/W	Lmm	CODE*
15	1655	110	562	90497L002
22	2483	113	842	90497L003
30	3310	110	1122	90497L004
35	4138	118	1402	90497L005
42	4965	118	1682	90497L006
52	5793	111	1964	90497L007
60	6620	110	2244	90497L008
65	7448	115	2524	90497L009
70	8275	118	2804	90497L010

Colour temp.	
3000K	3
4000K	0
Tunable White ³	T

INNER PROFILE | ASYMMETRIC



ASYM - Diffuser



W	lm output	lm/W	Lmm	CODE*
16	1396	87	562	90500L002
23	2095	91	842	90500L003
29	2793	96	1122	90500L004
36	3491	97	1402	90500L005
44	4189	95	1682	90500L006
52	4888	94	1964	90500L007
58	5586	96	2244	90500L008
65	6284	97	2524	90500L009
73	6982	96	2804	90500L010

¹ Prepared for emergency remote control.

² Versions DALI + EM 3h (K3) only available from L1402 mm.

³ Only available on dimmable DALI versions without emergency unit (No EM). Not available in L562 mm version.

03. Select options

OPTIONS	Code*
SwitchDIM Tunable White	926600
<ul style="list-style-type: none"> Each SwitchDIM Tunable White allows the control up to 20 luminaires of L ≤ 1682 mm and up to 10 luminaires of L ≥ 1964 mm. 	
Suspension	
S5 L1500 mm (x1)	910408
S5 L1500 mm (x2)	910409
S5 L3000 mm (x1)	910419
S5 L3000 mm (x2)	910412
S5 L6000 mm (x1)	910420
S5 L6000 mm (x2)	910421
Transparent current supply cable	
L1500 mm - 3 x 0,75 mm ²	940400
L1500 mm - 5 x 0,75 mm ²	940500
L1500 mm - 7 x 0,75 mm ²	940600
L3000 mm - 3 x 0,75 mm ²	940401
L3000 mm - 5 x 0,75 mm ²	940501
L3000 mm - 7 x 0,75 mm ²	940601
L6000 mm - 3 x 0,75 mm ²	940402
L6000 mm - 5 x 0,75 mm ²	940507
L6000 mm - 7 x 0,75 mm ²	940602
<ul style="list-style-type: none"> For the option DALI with emergency unit and remote control add 2 current supply cables of 5 x 0,75 mm². 	
Square ceiling rose	
Surface mounted T25  45 100	978610
Surface mounted T29 (DALI+K3) 	978611
Recessed T7  Ø70 35 90	971400
Recessed T59 (DALI+K3) 	971410
Round ceiling rose	
Surface mounted T24  45 Ø95	978600
Surface mounted T26 (DALI+K3) 	978601
Recessed T5  Ø70 33 Ø90	971300
Recessed T27 (DALI+K3) 	978700
Low Output version	
<ul style="list-style-type: none"> Under request. 	



*Replace the symbols to complete the code

Colour	▲
□ White	W
■ Black	B



Product details



