

REBA 65 D/I Line



Product characteristics

Body
Extruded aluminium profile

Finish
Powder coated

Optical system
bGLARE - Microprismatic diffuser
bLINE - Opal diffuser
ASYM - Asymmetric diffuser

Light source
LED, RG1, CRI>80, MacAdam Step ≤ 3

LED lifetime
80.000h @ L90, B10, Ta 25°C

Control gear
LED driver 220-240V-50/60Hz included




01. Select Outer Profile



OUTER PROFILE

Start / End (SRT/END)




Lmm	CODE*
1127	90512L0040▲0083
1407	90512L0050▲0083
1687	90512L0060▲0083
2249	90512L0080▲0083
2529	90512L0090▲0083
2809	90512L0100▲0083

*Replace the symbols to complete the code


Colour	▲
□ White	W
■ Grey	G
■ Black	B

Middle (MID)



Lmm	CODE*
1122	90512L0040▲0000
1402	90512L0050▲0000
1682	90512L0060▲0000
2244	90512L0080▲0000
2524	90512L0090▲0000
2804	90512L0100▲0000

Horizontal corner (HRZ) - Horizontal edge corner (EDGE)



Lmm	CODE*
608	90512H0040▲0000


OUTER PROFILE

- The indirect light diffuser is included on the product.
- To complete the product add the inner profile. Please order separately.
- For suspended version add the suspension, current supply cable and ceiling rose. Please order separately.
- To complete the line add the start kit, through-wiring and body connector kit. Please order separately.
- Dimensions do not include start kit. To complete the line add 6 mm to the length.
- The maximum line length with 1 single feeding point is 15000 mm.


02. Select Inner and Outer Profile




INNER PROFILE | SYMMETRIC




bGLARE - Microprismatic diffuser (60%/40%)



W	lm output	lm/W	Lmm	CODE*	
52	5250	101	1122	90532L004♥W0♦00	
65	6749	104	1402	90532L005♥W0♦00	
77	8249	107	1682	90532L006♥W♦♦00	
102	10499	103	2244	90532L008♥W0♦00	
117	11999	103	2524	90532L009♥W0♦00	
130	13499	104	2804	90532L010♥W0♦00	
HRZ	45	4500	100	604	90532H004♥W0♦00



bLINE - Opal diffuser (60%/40%)



W	lm output	lm/W	Lmm	CODE*	
52	5340	103	1122	90531L004♥W0♦00	
65	6866	106	1402	90531L005♥W0♦00	
77	8392	109	1682	90531L006♥W♦♦00	
102	10680	105	2244	90531L008♥W0♦00	
117	12206	104	2524	90531L009♥W0♦00	
130	13732	106	2804	90531L010♥W0♦00	
HRZ	45	4577	102	604	90531H004♥W0♦00


*Replace the symbols to complete the code

Control gear	Symbol
HF	E
DALI	H
HF+CD ¹	Q
SWD+CD ²	Y


Emergency	Symbol
No EM	0
EM 3h (K3) ³	3

Colour temp.	Symbol
3000K	3
4000K	0
Tunable White ⁴	T

INNER PROFILE | ASYMMETRIC



ASYM - Diffuser (60%/40%)



W	lm output	lm/W	Lmm	CODE*	
51	4888	96	1122	90534L004♥W0♦00	
66	6284	95	1402	90534L005♥W0♦00	
79	7680	97	1682	90534L006♥W♦♦00	
100	9775	98	2244	90534L008♥W0♦00	
117	11172	95	2524	90534L009♥W0♦00	
133	12568	94	2804	90534L010♥W0♦00	
EDGE	44	4189	95	604	90534E004♥W0♦00
HRZ	44	4189	95	604	90534H004♥W0♦00

¹ HF + Double circuit.

² SwitchDIM + Double circuit.

³ Prepared for emergency remote control.

⁴ Only available for the DALI and SWD+CD without emergency unit versions (No EM).

03. Select options

OPTIONS	Code*
SwitchDIM Tunable White • Each SwitchDIM Tunable White allows the control up to 10 luminaires of L ≤ 1682 mm and up to 5 luminaires of L ≥ 1964 mm.	926600
Start kit - end cap start/end • 2 end caps included. 	923700▲
Through-wiring • Standard 3 x 1,5 mm ² 4 x 1,5 mm ² 5 x 1,5 mm ²	945650 948400 945750
• 2 x 1,5 mm² HF+K3 (x1) - L562 - L1682 mm HF+K3 (x2) - L1964 - L2804 mm	948000 948001
• 2 x 1,5 mm² + 5P terminal block DALI+K3 (x1) - L562 - L1682 mm DALI+K3 (x2) - L1964 - L2804 mm	948200 948201
• 2 x 1,5 mm² + 2 x 0,75 mm² + 5P terminal block K3+TEL (x1) - L562 - L1682 mm K3+TEL (x2) - L1964 - L2804 mm	948100 948101
Body connector kit • Steel body connector, screws included.	932210
Suspension S5 L1500 mm (x1) S5 L1500 mm (x2) S5 L3000 mm (x1) S5 L3000 mm (x2) S5 L6000 mm (x1) S5 L6000 mm (x2)	910408 910409 910419 910412 910420 910421
Transparent current supply cable 3 x 1,5 mm ² 5 x 1,5 mm ² 7 x 1,5 mm ² • For the option DALI with emergency unit and remote control, it is necessary to order 2 current supply cables of 5 x 1,5 mm ² .	94030▲ 94000▲ 94010▲
Square ceiling rose⁵ Surface mounted T25  978610▲ Surface mounted T29 (DALI+K3)  978611▲ Recessed T7  971400▲ Recessed T59 (DALI+K3)  971410▲	
Round ceiling rose⁵ Surface mounted T24  978600▲ Surface mounted T26 (DALI+K3)  978601▲ Recessed T5  971300▲ Recessed T27 (DALI+K3)  978700▲	
Blank part L1500 mm L3000 mm • Includes inner profile and aluminium blank cover.	993040▲ 993041▲
Low Output version • Under request.	
Bespoke projects • Under request.	



*Replace the symbols to complete the code

Length	▲
L1500 mm	0
L3000 mm	1
L6000 mm	2

Colour ⁵	▲
□ White	W
■ Grey	G
■ Black	B



Product details



⁵The ceiling roses are available only in White or Black colour.