

## REBA 65 /E



### Product characteristics

#### Body

Extruded aluminium profile

#### Finish

Powder coated

#### Fixing system

Brackets

#### Optical system

bGLARE - Microprismatic diffuser

bLINE - Opal diffuser

ASYM - Asymmetric diffuser

#### Light source

LED, RG1, CRI>80, MacAdam Step  $\leq 3$

#### LED lifetime

80.000h @ L90, B10, Ta 25°C

#### Control gear

LED driver 220-240V-50/60Hz included


#### Ceiling thickness

For ceilings between 1-25 mm



## 01. Select Outer Profile

### OUTER PROFILE



Lmm	$\beta$	CODE*
590	580	90525L0020▲0000
870	860	90525L0030▲0000
1150	1140	90525L0040▲0000
1430	1420	90525L0050▲0000
1710	1700	90525L0060▲0000
1992	1982	90525L0070▲0000
2272	2262	90525L0080▲0000
2552	2542	90525L0090▲0000
2832	2822	90525L0100▲0000



\*Replace the symbols to complete the code


Colour	Symbol
White	W
Grey	G
Black	B

### OUTER PROFILE


• To complete the product add the inner profile. Please order separately.

## 02. Select Inner and Outer Profile

### INNER PROFILE | SYMMETRIC



#### bGLARE - Microprismatic diffuser




W	lm output	lm/W	Lmm	CODE*
15	1577	105	562	90502L002▼W0◆00
22	2366	108	842	90502L003▼W0◆00
30	3155	105	1122	90502L004▼W0◆00
35	3944	113	1402	90502L005▼W0◆00
42	4732	113	1682	90502L006▼W0◆00
52	5521	106	1964	90502L007▼W0◆00
60	6310	105	2244	90502L008▼W0◆00
65	7099	109	2524	90502L009▼W0◆00
70	7887	113	2804	90502L010▼W0◆00


\*Replace the symbols to complete the code

Control gear	Symbol
HF	E
DALI	H

Emergency	Symbol
No EM	0
EM 3h (K3) <sup>1 2</sup>	3




#### bLINE - Opal diffuser




W	lm output	lm/W	Lmm	CODE*
15	1681	112	562	90501L002▼W0◆00
22	2521	115	842	90501L003▼W0◆00
30	3362	112	1122	90501L004▼W0◆00
35	4202	120	1402	90501L005▼W0◆00
42	5043	120	1682	90501L006▼W0◆00
52	5883	113	1964	90501L007▼W0◆00
60	6724	112	2244	90501L008▼W0◆00
65	7564	116	2524	90501L009▼W0◆00
70	8405	120	2804	90501L010▼W0◆00

Colour temp.	Symbol
3000K	3
4000K	0
Tunable White <sup>3</sup>	T

### INNER PROFILE | ASYMMETRIC



#### ASYM - Diffuser



W	lm output	lm/W	Lmm	CODE*
16	1474	92	562	90504L002▼W0◆00
23	2211	96	842	90504L003▼W0◆00
29	2948	102	1122	90504L004▼W0◆00
36	3685	102	1402	90504L005▼W0◆00
44	4422	101	1682	90504L006▼W0◆00
52	5159	99	1964	90504L007▼W0◆00
58	5896	102	2244	90504L008▼W0◆00
65	6633	102	2524	90504L009▼W0◆00
73	7370	101	2804	90504L010▼W0◆00

<sup>1</sup> Prepared for emergency remote control.

<sup>2</sup> Versions DALI + EM 3h (K3) only available from L1402 mm.

<sup>3</sup> Only available on dimmable DALI versions without emergency unit (No EM). Not available in L562 mm version.

### 03. Select options

OPTIONS	Code
<b>SwitchDIM Tunable White</b> • Each SwitchDIM Tunable White allows the control up to 20 luminaires of L ≤ 1682 mm and up to 10 luminaires of L ≥ 1964 mm.	926600
<b>Steel safety cable</b> L1500 mm	955000
<b>Low Output version</b> • Under request.	

### Product details




Outer profile




Brackets



Inner profile symmetric



Inner profile asymmetric



Light uniformity



Clip-in diffuser



Ceiling recessed application



bGLARE diffuser



bLINE diffuser



ASYM diffuser



SwitchDIM  
Tunable White

