

REBA 65 /T



Product characteristics

Body
Extruded aluminium profile

Finish
Powder coated

Fixing system
Trimless recessed mounting kit

Optical system
bGLARE - Microprismatic diffuser
bLINE - Opal diffuser
ASYM - Asymmetric diffuser

Light source
LED, RG1, CRI>80, MacAdam Step ≤ 3

LED lifetime
80.000h @ L90, B10, Ta 25°C


Control gear
LED driver 220-240V-50/60Hz included

Ceiling thickness
For ceilings between 10, 13, 15 and 18 mm



01. Select Outer Profile

OUTER PROFILE



Lmm	Icon	CODE*
598	▣	90524L0020▲0000
878	▣	90524L0030▲0000
1158	▣	90524L0040▲0000
1438	▣	90524L0050▲0000
1718	▣	90524L0060▲0000
2000	▣	90524L0070▲0000
2280	▣	90524L0080▲0000
2560	▣	90524L0090▲0000
2840	▣	90524L0100▲0000



*Replace the symbols to complete the code


Colour	Symbol
White	▣
Grey	▣
Black	▣

OUTER PROFILE


• To complete the product add the inner profile. Please order separately.

02. Select Inner and Outer Profile

INNER PROFILE | SYMMETRIC



bGLARE - Microprismatic diffuser



W	lm output	lm/W	Lmm	CODE*
15	1577	105	562	90502L002▼W0◆00
22	2366	108	842	90502L003▼W0◆00
30	3155	105	1122	90502L004▼W0◆00
35	3944	113	1402	90502L005▼W0◆00
42	4732	113	1682	90502L006▼W0◆00
52	5521	106	1964	90502L007▼W0◆00
60	6310	105	2244	90502L008▼W0◆00
65	7099	109	2524	90502L009▼W0◆00
70	7887	113	2804	90502L010▼W0◆00

*Replace the symbols to complete the code


Control gear	Symbol
HF	▼
DALI	▼

Emergency	Symbol
No EM	●
EM 3h (K3) ^{1 2}	●

Colour temp.	Symbol
3000K	◆
4000K	◆
Tunable White ³	T




bLINE - Opal diffuser




W	lm output	lm/W	Lmm	CODE*
15	1681	112	562	90501L002▼W0◆00
22	2521	115	842	90501L003▼W0◆00
30	3362	112	1122	90501L004▼W0◆00
35	4202	120	1402	90501L005▼W0◆00
42	5043	120	1682	90501L006▼W0◆00
52	5883	113	1964	90501L007▼W0◆00
60	6724	112	2244	90501L008▼W0◆00
65	7564	116	2524	90501L009▼W0◆00
70	8405	120	2804	90501L010▼W0◆00

INNER PROFILE | ASYMMETRIC



ASYM - Diffuser



W	lm output	lm/W	Lmm	CODE*
16	1474	92	562	90504L002▼W0◆00
23	2211	96	842	90504L003▼W0◆00
29	2948	102	1122	90504L004▼W0◆00
36	3685	102	1402	90504L005▼W0◆00
44	4422	101	1682	90504L006▼W0◆00
52	5159	99	1964	90504L007▼W0◆00
58	5896	102	2244	90504L008▼W0◆00
65	6633	102	2524	90504L009▼W0◆00
73	7370	101	2804	90504L010▼W0◆00

¹ Prepared for emergency remote control.

² Versions DALI + EM 3h (K3) only available from L1402 mm.

³ Only available on dimmable DALI versions without emergency unit (No EM). Not available in L562 mm version.

03. Select options

OPTIONS	Code
SwitchDIM Tunable White • Each SwitchDIM Tunable White allows the control up to 20 luminaires of L ≤ 1682 mm and up to 10 luminaires of L ≥ 1964 mm.	926600
Steel safety cable L1500 mm	955000
Low Output version • Under request.	

Product details



Outer profile



Inner profile symmetric



Inner profile asymmetric




Light uniformity



Trimless recessed mounting kit



Clip-in diffuser



Trimless application



bGLARE diffuser



bLINE diffuser



ASYM diffuser



SwitchDIM Tunable White

