

ROFY 60 D/I



Product characteristics

Body

Aluminium

Finish

Powder coated

Optical system

gCONTROL+ - Microprismatic diffuser
LIGHT+ - Opal diffuser

Light source

LED, RG1, CRI>80, MacAdam Step ≤3

LED lifetime

80.000h @ L90, B10, Ta 25°C

Control gear

LED driver 220-240V-50/60Hz included



230V/50Hz



IP 40


IK 04

650°C


01. Select version



ROFY 60 D/I




gCONTROL+ - Microprismatic diffuser (80%/20%)



UGR	W	lm output	lm/W	Dmm	CODE*
≤19	32	3907	122	Ø400	90587L400▼▲◆0◆00
≤19	56	7286	130	Ø600	90587L600▼▲◆◆◆00
≤19	84	10892	130	Ø900	90587L900▼▲◆◆◆00
≤19	137	17867	130	Ø1150	90587L115▼▲◆◆◆00

LIGHT+ - Opal diffuser (80%/20%)



UGR	W	lm output	lm/W	Dmm	CODE*
≤22	32	4242	133	Ø400	90589L400▼▲◆0◆00
≤22	56	7910	141	Ø600	90589L600▼▲◆◆◆00
≤22	84	11826	141	Ø900	90589L900▼▲◆◆◆00
≤22	137	19398	142	Ø1150	90589L115▼▲◆◆◆00

ROFY 60 D/I

- For suspended version add current supply cable, suspension and ceiling rose. Please order separately.
- In order to guarantee total light uniformity on the ceiling in the suspended version, installation must be carried out at a minimum distance of 500 mm.

*Replace the symbols to complete the code

Control gear	▼
HF	E
DALI	H
HF+CD ¹	Q
SWD+CD ²	Y

Colour ³	▲
White	W
Grey	G
Black	B
Sahara	0
Mist	1
Carbon	I
Autumn	L
Rusty chain	R
Jungle	N
Golden eye	D
Old rose	5
Copper	7

Emergency	●
No EM	0
EM 3h (K3) ⁴	3

Colour temp.	◆
3000K	3
4000K	0
Tunable White	T

¹ HF + Double circuit.

² SwitchDIM + Double circuit.

³ See page 164.

⁴ Prepared for emergency remote control. Only available for the Ø600, Ø900 and Ø1150 mm versions.

02. Select options

OPTIONS Code*

Suspension

S10 L1500 mm (x3)	9111001
S10 L3000 mm (x3)	9111002
S10 L6000 mm (x3)	9111003

Transparent current supply cable

L1500 mm - 3 x 0,75 mm ²	940400
L1500 mm - 5 x 0,75 mm ²	940500
L1500 mm - 7 x 0,75 mm ²	940600
L3000 mm - 3 x 0,75 mm ²	940401
L3000 mm - 5 x 0,75 mm ²	940501
L3000 mm - 7 x 0,75 mm ²	940601
L6000 mm - 3 x 0,75 mm ²	940402
L6000 mm - 5 x 0,75 mm ²	940507
L6000 mm - 7 x 0,75 mm ²	940602

• For the DALI option with emergency unit and remote control add 2 current supply cables of 5 x 0,75 mm².

Round ceiling rose

Surface mounted T24	45 l		Ø95	978600♣
Surface mounted T26 (DALI+K3)				978601♣

Recessed T5	Ø70	33 l		Ø90	971300♣
Recessed T27 (DALI+K3)					978700♣


Central ceiling rose

Surface mounted T21	45 l		Ø95	977211♣
Surface mounted T28 (DALI+K3)				977230♣

Suspension rod

D95 - Ø400, Ø600 mm	913000♣
D120 - Ø900, Ø1150 mm	913010♣

• Ceiling rose included.



Low Output version

• Under request.



*Replace the symbols to complete the code

Colour	♣
<input type="checkbox"/> White	W
<input checked="" type="checkbox"/> Black	B




Product details



Ceiling surface application



Suspended application



Wall mounted



gCONTROL+ diffuser



LIGHT+ diffuser



Indirect light



Outer parallel suspension



Inner parallel suspension



Outer central suspension



Inner central suspension



Suspension rod

