

## ROFY 60 /T D/I



### Product characteristics

**Body**  
Aluminium

**Finish**  
Powder coated


**Optical system**  
gCONTROL+ - Microprismatic diffuser  
LIGHT+ - Opal diffuser

**Light source**  
LED, RG1, CRI>80, MacAdam Step  $\leq 3$

**LED lifetime**  
80.000h @ L90, B10, Ta 25°C

**Control gear**  
LED driver 220-240V-50/60Hz included

**Ceiling thickness**  
For ceilings between 9,5-18 mm




## 01. Select version

### ROFY 60 /T D/I




#### gCONTROL+ - Microprismatic diffuser (80%/20%)



UGR	W	lm output	lm/W	Hmm	Dmm	Ø	Ø	CODE*
≤19	32	3683	115	119	Ø400	Ø523	90591L400	▼▲◆0◆00
≤19	56	6869	123	119	Ø600	Ø723	90591L600	▼▲◆◆◆00
≤19	84	10270	122	135	Ø900	Ø1023	90591L900	▼▲◆◆◆00
≤19	137	16846	123	135	Ø1150	Ø1273	90591L1150	▼▲◆◆◆00

#### LIGHT+ - Opal diffuser (80%/20%)



UGR	W	lm output	lm/W	Hmm	Dmm	Ø	Ø	CODE*
≤22	32	3851	120	119	Ø400	Ø523	90593L400	▼▲◆0◆00
≤22	56	7182	128	119	Ø600	Ø723	90593L600	▼▲◆◆◆00
≤22	84	10736	128	135	Ø900	Ø1023	90593L900	▼▲◆◆◆00
≤22	137	17612	129	135	Ø1150	Ø1273	90593L1150	▼▲◆◆◆00

### ROFY 60 /T D/I

• This product cannot be installed on the wall.



\*Replace the symbols to complete the code

Control gear	
HF	E
DALI	H
HF+CD <sup>1</sup>	Q
SWD+CD <sup>2</sup>	Y

Colour <sup>3</sup>	
White	W
Grey	G
Black	B
Sahara	0
Mist	1
Carbon	I
Autumn	L
Rusty chain	R
Jungle	N
Golden eye	D

Emergency	
No EM	0
EM 3h (K3) <sup>4</sup>	3

Colour temp.	
3000K	3
4000K	0
Tunable White	T

## 02. Select options

OPTIONS	Code
<b>Tilted bracket</b>	
Ø400 mm	927100
Ø600 mm	927101
Ø900 mm	927102
Ø1150 mm	927103
<b>Steel safety cable</b>	
L1500 mm	955000
<b>Low Output version</b>	
• Under request.	




### Product details



Trimless application

Tilted bracket



gCONTROL+ diffuser

LIGHT+ diffuser

<sup>1</sup> HF + Double circuit.

<sup>2</sup> SwitchDIM + Double circuit.

<sup>3</sup> See page 164.

<sup>4</sup> Prepared for emergency remote control. Only available for the Ø600, Ø900 and Ø1150 mm versions.