

ROFY 85 D/I



Product characteristics

Body

Aluminium

Finish

Powder coated

Optical system

gCONTROL+ - Microprismatic diffuser
LIGHT+ - Opal diffuser

Light source

LED, RG1, CRI>80, MacAdam Step ≤ 3

LED lifetime

80.000h @ L90, B10, Ta 25°C

Control gear

LED driver 220-240V-50/60Hz included



230V/50Hz



IP 40


K 04

650°C


01. Select version



ROFY 85 D/I




gCONTROL+ - Microprismatic diffuser (80%/20%)



| UGR | W | lm output | lm/W | Dmm | CODE* |
|-----|-----|-----------|------|-------|----------------|
| ≤19 | 32 | 4018 | 126 | Ø400 | 90624L400♥♣♦0 |
| ≤19 | 56 | 7494 | 134 | Ø600 | 90624L600♥♣♦♦0 |
| ≤19 | 84 | 11203 | 133 | Ø900 | 90624L900♥♣♦♦0 |
| ≤19 | 137 | 18377 | 134 | Ø1150 | 90624L115♥♣♦♦0 |

LIGHT+ - Opal diffuser (80%/20%)



| UGR | W | lm output | lm/W | Dmm | CODE* |
|-----|-----|-----------|------|-------|----------------|
| ≤22 | 32 | 4242 | 133 | Ø400 | 90623L400♥♣♦♦0 |
| ≤22 | 56 | 7910 | 141 | Ø600 | 90623L600♥♣♦♦0 |
| ≤22 | 84 | 11826 | 141 | Ø900 | 90623L900♥♣♦♦0 |
| ≤22 | 137 | 19398 | 142 | Ø1150 | 90623L115♥♣♦♦0 |

ROFY 85 D/I

- To complete the product add current supply cable, suspension and ceiling rose. Please order separately.
- In order to guarantee a total uniformity of light on the ceiling, the installation must be done at a minimum distance of 500 mm.

*Replace the symbols to complete the code

| Control gear | |
|---------------------|---|
| HF | E |
| DALI | H |
| HF+CD ¹ | Q |
| SWD+CD ² | Y |

| Colour ³ | |
|---------------------|---|
| White | W |
| Grey | G |
| Black | B |
| Sahara | 0 |
| Mist | 1 |
| Carbon | I |
| Autumn | L |
| Rusty chain | R |
| Jungle | N |
| Golden eye | D |

| Emergency | |
|-------------------------|---|
| No EM | 0 |
| EM 3h (K3) ⁴ | 3 |

| Colour temp. | |
|---------------|---|
| 3000K | 3 |
| 4000K | 0 |
| Tunable White | T |

¹ HF + Double circuit.

² SwitchDIM + Double circuit.

³ See page 164.

⁴ Prepared for emergency remote control. Only available for the Ø600, Ø900 and Ø1150 mm versions.

02. Select options

OPTIONS Code*

Suspension

| | |
|-------------------|---------|
| S10 L1500 mm (x3) | 9111001 |
| S10 L3000 mm (x3) | 9111002 |
| S10 L6000 mm (x3) | 9111003 |

Transparent current supply cable

| | |
|-------------------------------------|--------|
| L1500 mm - 3 x 0,75 mm ² | 940400 |
| L1500 mm - 5 x 0,75 mm ² | 940500 |
| L1500 mm - 7 x 0,75 mm ² | 940600 |
| L3000 mm - 3 x 0,75 mm ² | 940401 |
| L3000 mm - 5 x 0,75 mm ² | 940501 |
| L3000 mm - 7 x 0,75 mm ² | 940601 |
| L6000 mm - 3 x 0,75 mm ² | 940402 |
| L6000 mm - 5 x 0,75 mm ² | 940507 |
| L6000 mm - 7 x 0,75 mm ² | 940602 |

• For the DALI option with emergency unit and remote control add 2 current supply cables of 5 x 0,75 mm².

Round ceiling rose

| | | | | |
|-------------------------------|------|--|-----|---------|
| Surface mounted T24 | 45 l | | Ø95 | 978600♣ |
| Surface mounted T26 (DALI+K3) | | | | 978601♣ |

| | | | | | |
|------------------------|-----|------|--|-----|---------|
| Recessed T5 | Ø70 | 33 l | | Ø90 | 971300♣ |
| Recessed T27 (DALI+K3) | | | | | 978700♣ |


Central ceiling rose

| | | | | |
|-------------------------------|------|--|-----|---------|
| Surface mounted T21 | 45 l | | Ø95 | 977211♣ |
| Surface mounted T28 (DALI+K3) | | | | 977230♣ |

Suspension rod

| | |
|-----------------------|---------|
| D95 - Ø400, Ø600 mm | 913000♣ |
| D120 - Ø900, Ø1150 mm | 913010♣ |

• Ceiling rose included.



Low Output version

• Under request.



*Replace the symbols to complete the code

| | |
|---|---|
| Colour | ♣ |
| <input type="checkbox"/> White | W |
| <input checked="" type="checkbox"/> Black | B |



Product details



Suspended application



Indirect light



gCONTROL+ diffuser



LIGHT+ diffuser



Outer parallel suspension



Inner parallel suspension



Outer central suspension



Inner central suspension



Suspension rod

