

ROFY 85 /E



Product characteristics

Body
Aluminium

Finish
Powder coated


Optical system
gCONTROL+ - Microprismatic diffuser
LIGHT+ - Opal diffuser

Light source
LED, RG1, CRI>80, MacAdam Step ≤3

LED lifetime
80.000h @ L90, B10, Ta 25°C

Control gear
LED driver 220-240V-50/60Hz included

Ceiling thickness
For ceilings between 1-25 mm




01. Select version

ROFY 85 /E




gCONTROL+ - Microprismatic diffuser



UGR	W	lm output	lm/W	Dmm	Ø	Ø	CODE*
≤19	16	1810	113	Ø300	Ø286		90622L300▼▲◆0◆00
≤19	24	2871	120	Ø400	Ø386		90622L400▼▲◆0◆00
≤19	43	5526	129	Ø600	Ø586		90622L600▼▲◆0◆00
≤19	65	8230	127	Ø900	Ø886		90622L900▼▲◆0◆00
≤19	107	13429	126	Ø1150	Ø1136		90622L115▼▲◆0◆00

LIGHT+ - Opal diffuser



UGR	W	lm output	lm/W	Dmm	Ø	Ø	CODE*
≤25	16	2135	133	Ø300	Ø286		90621L300▼▲◆0◆00
≤25	24	3385	141	Ø400	Ø386		90621L400▼▲◆0◆00
≤22	43	6516	152	Ø600	Ø586		90621L600▼▲◆0◆00
≤22	65	9704	149	Ø900	Ø886		90621L900▼▲◆0◆00
≤22	107	15835	148	Ø1150	Ø1136		90621L115▼▲◆0◆00

ROFY 85 /E

• This product cannot be installed on the wall.



*Replace the symbols to complete the code

Control gear	
HF	E
DALI	H

Colour ¹	
White	W
Grey	G
Black	B
Sahara	0
Mist	1
Carbon	I
Autumn	L
Rusty chain	R
Jungle	N
Golden eye	D

Emergency	
No EM	0
EM 3h (K3) ²	3

Colour temp.	
3000K	3
4000K	0
Tunable White ³	T

02. Select options


OPTIONS Code

Steel safety cable 955000

Low Output version

• Under request.

Product details



Ceiling recessed application



gCONTROL+ diffuser



LIGHT+ diffuser

¹ See page 164.

² Prepared for emergency remote control. Only available for the Ø600, Ø900 and Ø1150 mm versions.

³ Not available in the Ø300 version.