

## ROFY 85 IP /C



### Product characteristics

#### Body

Aluminium

#### Finish

Powder coated

#### Optical system

LIGHT+ - Opal diffuser

#### Light source


LED, RG1, CRI>80, MacAdam Step ≤3

#### LED lifetime

80.000h @ L90, B10, Ta 25°C


#### Control gear

LED driver 220-240V-50/60Hz included




## 01. Select version

ROFY 85 IP /C



### LIGHT+ - Opal diffuser



W	lm output	lm/W	Dmm	CODE*
16	2135	133	Ø300	90581L300▼▲◆0◆00
24	3385	141	Ø400	90581L400▼▲◆0◆00
43	6516	152	Ø600	90581L600▼▲◆0◆00



\*Replace the symbols to complete the code

Control gear	
HF	E
DALI	H

Colour <sup>1</sup>	
White	W
Grey	G
Black	B
Sahara	0
Mist	1
Carbon	I
Autumn	L
Rusty chain	R
Jungle	N
Golden eye	D

Emergency	
No EM	0
EM 3h (K3) <sup>2</sup>	3

Colour temp.	
3000K	3
4000K	0
Tunable White <sup>3</sup>	T

## 02. Select options

### OPTIONS

#### Low Output version

- Under request.



### Product details



Ceiling surface application



Wall mounted



LIGHT+ diffuser



IP54 protection

<sup>1</sup> See page 164.

<sup>2</sup> Prepared for emergency remote control. Only available for the Ø600 mm.

<sup>3</sup> Not available in versions Ø300 mm.