

ROFY 85 IP /E



Product characteristics

Body

Aluminium

Finish

Powder coated

Optical system

LIGHT+ - Opal diffuser

Light source

LED, RG1, CRI>80, MacAdam Step ≤3

LED lifetime

80.000h @ L90, B10, Ta 25°C

Control gear

LED driver 220-240V-50/60Hz included

Ceiling thickness

For ceilings between 1-35 mm




01. Select version

ROFY 85 IP / E



LIGHT+ - Opal diffuser



W	lm output	lm/W	Dmm	Ø	CODE*
16	2135	133	Ø323	Ø305	90573L300▼▲0◆00
24	3385	141	Ø423	Ø405	90573L400▼▲0◆00
43	6516	152	Ø623	Ø605	90573L600▼▲0◆00

ROFY 85 IP / E

• This product cannot be installed on the wall.



*Replace the symbols to complete the code

Control gear	
HF	E
DALI	H

Colour 1 ▲

White	W
Grey	G
Black	B
Sahara	0
Mist	1
Carbon	I
Autumn	L
Rusty chain	R
Jungle	N
Golden eye	D

Emergency ●

No EM	0
EM 3h (K3) ²	3

Colour temp. ◆

3000K	3
4000K	0
Tunable White ³	T

02. Select options

OPTIONS Code

Steel safety cable


L1500 mm 955000

Low Output version

• Under request.



Product details



Ceiling recessed application



LIGHT+ diffuser

¹ See page 164.

² Prepared for emergency remote control. Only available for the Ø600 mm.

³ Not available in versions Ø300 mm.