

## TALEA Glare /C




### Product characteristics

---


<b>Body</b> Extruded aluminium profile
<b>End caps</b> Injected polycarbonate
<b>Finish</b> Anodized in natural colour
<b>Optical system</b> bLINE - Opal diffuser
<b>Light source</b> LED, RG1, CRI>80, MacAdam Step ≤3
<b>LED lifetime</b> 80.000h @ L90, B10, Ta 25°C
<b>Control gear</b> LED driver 220-240V-50/60Hz included

---




# 01. Select version

## TALEA Glare /C



### bLINE - Opal diffuser



UGR	W	lm output	lm/W	Lmm	CODE*
≤19	15	1802	120	878	90429L130▼▲♦00
≤19	19	2402	126	1158	90429L140▼▲♦♦00
≤19	23	3003	131	1438	90429L150▼▲♦♦00
≤19	27	3604	133	1718	90429L160▼▲♦♦00
≤19	32	4204	131	1998	90429L170▼▲♦♦00
≤19	35	4805	137	2278	90429L180▼▲♦♦00
≤19	41	5405	132	2558	90429L190▼▲♦♦00
≤19	43	6006	140	2838	90429L100▼▲♦♦00



\*Replace the symbols to complete the code

#### Control gear ▼

HF	E
DALI	H

#### Colour<sup>1</sup> ▲

□ White	W
■ Grey	G
■ Black	B

#### Emergency ●

No EM	0
EM 3h (K3) <sup>2</sup>	3

#### Colour temp. ♦

3000K	3
4000K	0

## Product details



Ceiling surface application



Wall application



bLINE diffuser



Clip-in diffuser



Light uniformity

<sup>1</sup> End cap colour.

<sup>2</sup> 3h emergency unit with self-test. Only available in HF versions.