

TALEA Glare



Product characteristics


Body

Extruded aluminium profile



End caps

Injected polycarbonate



Finish

Anodized in natural colour



Optical system

bLINE - Opal diffuser



Wiring

Pre-wired with 1500 mm transparent current supply cable included

Light source

LED, RG1, CRI>80, MacAdam Step ≤ 3

LED lifetime

80.000h @ L90, B10, Ta 25°C

Control gear

Not included


01. Select version



TALEA Glare



bLINE - Opal diffuser



UGR	W	lm output	lm/W	Lmm	CODE*
≤19	15	1802	120	878	90428L1300▲◆00
≤19	19	2402	126	1158	90428L1400▲◆◆00
≤19	23	3003	131	1438	90428L1500▲◆◆00
≤19	27	3604	133	1718	90428L1600▲◆◆00
≤19	32	4204	131	1998	90428L1700▲◆◆00
≤19	35	4805	137	2278	90428L1800▲◆◆00
≤19	41	5405	132	2558	90428L1900▲◆◆00
≤19	43	6006	140	2838	90428L1000▲◆◆00

*Replace the symbols to complete the code

Colour ¹	Symbol
White	W
Grey	G
Black	B

Emergency	Symbol
No EM	0
EM 3h (K3) ²	3

TALEA Glare

• To complete the product add the suspension and ceiling rose. Please order separately.


Colour temp.	Symbol
3000K	3
4000K	0

02. Select ceiling rose


Recessed - No EM



Recessed - EM 3h (K3)



Surface mounted - No EM



Surface mounted - EM 3h (K3)



HF

	CODE*
L878	978401▲
L1158	978402▲
L1438	978403▲
L1718	978404▲
L1998	978405▲
L2278	978406▲
L2558	978407▲
L2838	978408▲

HF + EM 3h (K3)

	CODE*
L1158	978432▲
L1438	978433▲
L1718	978434▲
L1998	978435▲
L2278	978436▲
L2558	978437▲
L2838	978438▲

HF

	CODE*
L878	978201▲
L1158	978202▲
L1438	978203▲
L1718	978204▲
L1998	978205▲
L2278	978206▲
L2558	978207▲
L2838	978208▲

HF + EM 3h (K3)

	CODE*
L1158	978232▲
L1438	978233▲
L1718	978234▲
L1998	978235▲
L2278	978236▲
L2558	978237▲
L2838	978238▲

DALI

	CODE*
L878	978501▲
L1158	978502▲
L1438	978503▲
L1718	978504▲
L1998	978505▲
L2278	978506▲
L2558	978507▲
L2838	978508▲

DALI + EM 3h (K3)

	CODE*
L1158	978532▲
L1438	978533▲
L1718	978534▲
L1998	978535▲
L2278	978536▲
L2558	978537▲
L2838	978538▲

DALI

	CODE*
L878	978301▲
L1158	978302▲
L1438	978303▲
L1718	978304▲
L1998	978305▲
L2278	978306▲
L2558	978307▲
L2838	978308▲

DALI + EM 3h (K3)

	CODE*
L1158	978332▲
L1438	978333▲
L1718	978334▲
L1998	978335▲
L2278	978336▲
L2558	978337▲
L2838	978338▲

CEILING ROSE

- Control gear included in the ceiling rose.
- The maximum distance between the ceiling rose and the product is 3000 mm.


¹ End cap colour.

² Prepared for emergency remote control.

03. Select options

OPTIONS	Code
Suspension	
S5 L1500 mm (x2)	910409
S5 L3000 mm (x2)	910412
Current supply cable	
• HF/DALI	
L3000 mm - 2 x 0,75 mm ²	942801
• HF/DALI + EM 3h (K3)	
L3000 mm - 5 x 0,75 mm ²	940501

Product details



Suspended application




bLINE diffuser



Clip-in diffuser



Light uniformity



Ceiling roses

