


TALEA Line



Product characteristics


Body Extruded aluminium profile
End caps Injected polycarbonate
Finish Anodized in natural colour
Optical system bLINE - Opal diffuser
Wiring Pre-wired with 1500 mm transparent current supply cable included in the Start modules (SRT)
Light source LED, RG1, CRI>80, MacAdam Step ≤ 3
LED lifetime 80.000h @ L90, B10, Ta 25°C
Control gear LED driver 220-240V-50/60Hz included




01. Select version



TALEA Line



bLINE - Opal diffuser



W	lm output	lm/W	Lmm	CODE*
19	2340	123	590	90439L220▼00♣♣
27	3510	130	870	90439L230▼00♣♣
35	4680	134	1150	90439L240▼00♣♣♣
43	5850	136	1430	90439L250▼00♣♣♣♣
54	7020	130	1710	90439L260▼00♣♣♣♣♣
62	8190	132	1990	90439L270▼00♣♣♣♣♣♣
70	9360	134	2270	90439L280▼00♣♣♣♣♣♣♣
78	10530	135	2550	90439L290▼00♣♣♣♣♣♣♣♣
86	11700	136	2830	90439L200▼00♣♣♣♣♣♣♣♣♣

*Replace the symbols to complete the code

Module direction ▲
LEFT L
RIGHT R


Control gear ▼
HF E
DALI H

Emergency ●
No EM 0
EM 3h (K3)¹ 3


Colour temp. ◆
3000K 3
4000K 0

Module ♣
SRT 49
MID 00
END 50

TALEA HRZ



bLINE - Opal diffuser



W	lm output	lm/W	CODE*
35	4680	134	90754▲220▼00♣♣

AVAILABLE MODULES







Start module (SRT)
 Middle module (MID)
 End module (END)

TALEA Line

- For surface application add surface mounting kit. Please order separately.
- For suspended application add the suspension and ceiling rose. Please order separately.
- To complete the line add the start kit and body connector kit. Please order separately.
- Dimensions do not include start kit. To complete the line add 8 mm to the length.

¹ 3h emergency unit with self-test. Only available in HF versions.

02. Select options

OPTIONS		Code*
Start kit - End cap start/end		
White		922700
Grey		922701
Black		922702
• 2 end caps included.		
Body connector kit		
HF (x1)		931801
HF + K3 (x1)		931802
DALI (x1)		931800
• Body connector in injected polycarbonate.		
Surface mounting kit		
TALEA (x2)		926400
TALEA HRZ (x4)		926410
Suspension		
• For TALEA:		
S5 L1500 mm (x2)		910409
S5 L3000 mm (x2)		910412
S5 L6000 mm (x2)		910421
• For TALEA HRZ:		
S5 L1500 mm (x3)		910423
S5 L3000 mm (x3)		910424
S5 L6000 mm (x3)		910425
Current supply cable		
L3000 mm - 5 x 1,5 mm ²		940001
L6000 mm - 5 x 1,5 mm ²		940002
Round ceiling rose		
Surface mounted T24 D95	 45  Ø95	978600♣
Recessed T5 D90	 Ø70 33  Ø90	971300♣




*Replace the symbols to complete the code


Colour 
 White W
 Black B



Product details




Ceiling surface application



Suspended application



Wall application



Talea HRZ



bLINE diffuser



Clip-in diffuser



Light uniformity



Surface mounting kit



Ceiling roses

