

Product characteristics

Body

Steel sheet

Frame

Aluminium

Finish

White matte powder coated

Fixing system

Pull-up: for plasterboard ceilings with brackets

Wiring

Pre-wired with 1000 mm long
H05VV-F cable

Optical system

DAM - Microprismatic diffuser
LIGHT+ - Opal diffuser

Light source

LED, RG1, CRI>80, MacAdam Step ≤ 3

LED lifetime


80.000h @ L80, B10, Ta 25°C

Control gear

LED driver 220-240V-50/60Hz included

Ceiling thickness

For ceilings between 2-60 mm




01. Select version




THE

*Replace the symbols to complete the code




DAM - Microprismatic diffuser



UGR	W	lm output	lm/W	LxWmm	⌈	CODE*
≤19	34	4225	124	1197x297	1180x288	90793L123▼W●000
≤19	42	5282	126	1497x297	1480x288	90793L153▼W●000
≤19	74	8911	120	1497x297	1480x288	90795L153▼W●000
≤19	34	4225	124	597x597	580x588	90793L066▼W●000
≤19	59	7129	121	597x597	580x588	90795L066▼W●000

LIGHT+ - Opal diffuser



UGR	W	lm output	lm/W	LxWmm	⌈	CODE*
≤22	34	4587	135	1197x297	1180x288	90794L123▼W●000
≤22	42	5734	137	1497x297	1480x288	90794L153▼W●000
≤25	74	9675	131	1497x297	1480x288	90796L153▼W●000
≤22	34	4587	135	597x597	580x588	90794L066▼W●000
≤22	59	7740	131	597x597	580x588	90796L066▼W●000

Control gear	
HF	E
DALI	H

Emergency	
No EM	0
EM 3h (K3) ¹	3

02. Select options



Product details

OPTIONS Code

Connector

3-pole Wieland GST18i3 male connector	965301
5-pole Wieland GST18i5 DIM male connector	965403

Steel safety cable

L1500 mm	955000
----------	--------

CRI>90

- Under request.

Bespoke projects

- Under request.



Pull-up recessed version detail



Brackets

¹ Prepared for emergency remote control.