

THS



Product characteristics

Body

Steel sheet

Frame

Aluminium

Finish

White matte powder coated

Optical system

DAM - Microprismatic diffuser
LIGHT+ - Opal diffuser

Light source

LED, RG1, CRI>80, MacAdam Step ≤3

LED lifetime

80.000h @ L80, B10, Ta 25°C

Control gear

LED driver 220-240V-50/60Hz included



230V/50Hz



IP 65


650°C

01. Select version




THS

*Replace the symbols to complete the code




DAM - Microprismatic diffuser



UGR	W	lm output	lm/W	LxWmm	CODE*
≤19	34	4225	124	1142x297	90801L123▼W●000
≤19	42	5282	126	1417x297	90801L153▼W●000
≤22	74	8911	120	1417x297	90803L153▼W●000
≤19	34	4225	124	597x597	90801L066▼W●000
≤19	59	7129	121	597x597	90803L066▼W●000

Control gear	
HF	E
DALI	H

LIGHT+ - Opal diffuser



UGR	W	lm output	lm/W	LxWmm	CODE*
≤22	34	4587	135	1142x297	90802L123▼W●000
≤22	42	5734	137	1417x297	90802L153▼W●000
≤25	74	9675	120	1417x297	90804L153▼W●000
≤22	34	4587	135	597x597	90802L066▼W●000
≤22	59	7740	121	597x597	90804L066▼W●000

Emergency	
No EM	0
EM 3h (K3) ¹	3

02. Select options

OPTIONS

- CRI>90**
- Under request.

¹ Prepared for emergency remote control.