

TTP 100



Product characteristics

Body

Polycarbonate tube

Finish

White matte powder coated
gear tray

Fixing system

Clamps not included

Optical system

TUP - Transparent diffuser
TOP - Opal diffuser

Wiring

1500 mm H07RN-F cable
and plastic cable gland included

Light source

LED, RG0, CRI>80, MacAdam Step ≤ 3

LED lifetime

80.000h @ L90, B10, Ta 25°C

Control gear

LED driver 220-240V-50/60Hz included




01. Select version

TTP 100


Aluminium end caps



Stainless steel end caps




TUP - Transparent diffuser



W	lm output	lm/W	Lmm	CODE*
23	3578	156	660	90481L060▼▲0◆00
33	5367	163	940	90481L090▼▲0◆00
45	7156	159	1220	90481L120▼▲0◆00
76	12556	165	1500	90496L150▼▲0◆00
95	15435	162	1500	90479L150▼▲0◆00

TOP - Opal diffuser



W	lm output	lm/W	Lmm	CODE*
23	3264	142	660	90480L060▼▲0◆00
33	4895	148	940	90480L090▼▲0◆00
45	6527	145	1220	90480L120▼▲0◆00
76	11388	150	1500	90495L150▼▲0◆00
95	13681	144	1500	90478L150▼▲0◆00

TTP 100

- To complete the product add the fixing system. Please order separately.
- For suspended version add the suspension and ceiling rose. Please order separately.
- The luminaire with sensor has 105 mm more than the standard length.



*Replace the symbols to complete the code

Control gear	▼
HF	E
DALI	H

End caps	▲
Aluminium	0
Stainless steel	S

Emergency	●
No EM	0
EM 3h (K3) ¹	3

Colour temp.	◆
3000K	3
4000K	0
Tunable White ²	T

¹ 3h emergency unit with self-test. Only available in HF versions. Not available in the 95W version.

² Only available for the DALI without emergency unit versions (No EM).

02. Select options

OPTIONS	Code*
SwitchDIM Tunable White • The SwitchDIM Tunable White allows the control of up to 20 luminaires. • For the L1500 mm version it only allows the control of up to 10 luminaires.	926600
Fixing system Stainless steel clamp A1 D100 (x2)	46  915503
Stainless steel clamp A2 D100 (x2)	72  915505
Stainless steel clamp with fast lock D100 (x2)	52  915504
Suspension S4 L1500 mm (x2)	910200
Ceiling rose ¹ Surface mounted T24 D95	45  Ø95 978600♣
Recessed T5 D90	 Ø70 33  Ø90 971300♣
Cable gland for HF versions Metal M16 (x1)	925000
Breathable metal M16 (x1)	926700
Cable gland for DALI versions Metal M20 (x1)	925001
Breathable metal M20 (x1)	926701
Sensor • Under request. • Detection range: 100%. Hold time: 5s. Daylight Threshold: disabled. For other types of programming, consult the sensor's instructions manual.	
Sensor and emergency unit (3 hours) • Under request.	



*Replace the symbols to complete the code

Colour ♣
 White W
 Black B



Product details



