

TUBULAR
LUMINAIRES

TTP 50 360 HRZ



Product characteristics

Body

Polycarbonate tube

Finish

Powder coated aluminium
end caps

Optical system

TOP - Opal diffuser

Light source

LED, RG0, CRI>80, MacAdam Step ≤3

LED lifetime

70.000h @ L80, B10, Ta 25°C

Control gear


Not included




01. Select version



TTP 50 360 HRZ



TOP - Opal diffuser



W	lm output	lm/W	Lmm	CODE*
10	912	91	572	90677L0600▲0◆00
18	1685	94	972	90677L0900▲0◆00
23	2275	99	1272	90677L1200▲0◆00
29	2916	101	1572	90677L1500▲0◆00
34	3370	99	1872	90677L1800▲0◆00
37	3744	101	2072	90677L2000▲0◆00

*Replace the symbols to complete the code

Colour	◆
□ White	W
■ Grey	G
■ Black	B

Colour temp.	◆
3000K	3
4000K	0

TTP 50 360 HRZ

• To complete the product add the suspension, current supply cable and ceiling rose. Please order separately.

02. Select ceiling rose

Recessed - T31 D90

33 |  Ø90

 Ø70


HF

	CODE*
L572, L972, L1272, L1572	972750♣
L1872, L2072	972751♣

DALI

	CODE*
L572, L972, L1272, L1572	972752♣
L1872, L207	972753♣

Surface mounted - T36 L350W50



HF

	CODE*
L572, L972, L1272, L1572	972770♣
L1872, L2072	972771♣

DALI

	CODE*
L572, L972, L1272, L1572	972772♣
L1872, L2072	972773♣



*Replace the symbols to complete the code

Colour	♣
<input type="checkbox"/> White	W
<input type="checkbox"/> Black	B

CEILING ROSE

- Control gear included in the ceiling rose.

03. Select options

OPTIONS Code

Suspension

- For recessed ceiling rose T31 D90:

S4 L1500 mm (x2)	910200
S4 L3000 mm (x2)	910204
S4 L6000 mm (x2)	910208

- For surface ceiling rose T36 L350W50:

S13 L1500 mm (x2)	913200
S13 L3000 mm (x2)	913201
S13 L6000 mm (x2)	913203

Transparent current supply cable


L1500 mm - 2 x 0,75 mm ²	942800
L3000 mm - 2 x 0,75 mm ²	942801
L6000 mm - 2 x 0,75 mm ²	942802



Product details



Suspension



Ceiling roses

