

TTP 50 360 VRT



Product characteristics

Body

Polycarbonate tube

Finish

Powder coated aluminium
end caps

Optical system

Polycarbonate

Light source

LED, RG0, CRI>80, MacAdam Step ≤3

LED lifetime

70.000h @ L80, B10, Ta 25°C

Control gear

Not included




01. Select version



TTP 50 360 VRT



TOP - Opal diffuser



W	lm output	lm/W	Lmm	CODE*
10	912	91	570	90555L0600▲0◆00
18	1685	94	970	90555L0900▲0◆00
23	2275	99	1270	90555L1200▲0◆00
29	2916	101	1570	90555L1500▲0◆00
34	3370	99	1870	90555L1800▲0◆00
37	3744	101	2070	90555L2000▲0◆00

*Replace the symbols to complete the code

Colour	▲
□ White	W
■ Grey	G
■ Black	B

Colour temp.	◆
3000K	3
4000K	0

TTP 50 360 VRT

- To complete the product add the suspension, current supply cable and ceiling rose. Please order separately.

02. Select ceiling rose

Recessed - T31 D90



Ø70


HF

	CODE*
L572, L972, L1272, L1572	972750♣
L1872, L2072	972751♣

DALI

	CODE*
L572, L972, L1272, L1572	972752♣
L1872, L2072	972753♣

Surface mounted - T32 D80



HF

	CODE*
L572, L972, L1272, L1572	972760♣
L1872, L2072	972761♣

DALI

	CODE*
L572, L972, L1272, L1572	972762♣
L1872, L2072	972763♣

CEILING ROSE

- Control gear included in the ceiling rose.

03. Select options

OPTIONS

Code

Transparent current supply cable

L1500 mm - 2 x 0,75 mm ²	942800
L3000 mm - 2 x 0,75 mm ²	942801
L6000 mm - 2 x 0,75 mm ²	942802

Bespoke projects

- Under request.



*Replace the symbols to complete the code

Colour

<input type="checkbox"/> White	W
<input type="checkbox"/> Black	B



Product details



Ceiling roses

