

TUBULAR
LUMINAIRES

TTP 70 Line



Product characteristics

Body

Polycarbonate tube

Finish

White matte powder coated gear tray

Fixing system

Clamps not included

Optical system

TUP - Transparent diffuser

TOP - Opal diffuser

Wiring

Plastic cable gland and through-wiring included

1500 mm H07RN-F cable not included

Light source


LED, RG0, CRI>80, MacAdam Step ≤ 3

LED lifetime

80.000h @ L90, B10, Ta 25°C

Control gear


LED driver 220-240V-50/60Hz included




01. Select version



LOW OUTPUT




TUP - Transparent diffuser



W	lm output	lm/W	Lmm	CODE*
12	1789	149	620	90489L060▼▲0◆♣
17	2684	158	900	90489L090▼▲0◆♣
21	3578	170	1180	90489L120▼▲0◆♣
26	4473	172	1460	90489L150▼▲0◆♣

TOP - Opal diffuser



W	lm output	lm/W	Lmm	CODE*
12	1691	141	620	90488L060▼▲0◆♣
17	2536	149	900	90488L090▼▲0◆♣
21	3382	161	1180	90488L120▼▲0◆♣
26	4227	163	1460	90488L150▼▲0◆♣

*Replace the symbols to complete the code


Control gear	
HF	E
DALI	H

End caps	
Polycarbonate ¹	0
Stainless steel ²	S


Colour temp.	
3000K	3
4000K	0
Tunable White ³	T

Module	
SRT/MID	58
END	50

HIGH OUTPUT




TUP - Transparent diffuser




W	lm output	lm/W	Lmm	CODE*
26	3765	145	620	90487L060▼▲0◆♣
40	5648	141	900	90487L090▼▲0◆♣
51	7531	148	1180	90487L120▼▲0◆♣
63	9413	149	1460	90487L150▼▲0◆♣

TOP - Opal diffuser



W	lm output	lm/W	Lmm	CODE*
26	3506	135	620	90486L060▼▲0◆♣
40	5259	131	900	90486L090▼▲0◆♣
51	7011	137	1180	90486L120▼▲0◆♣
63	8764	139	1460	90486L150▼▲0◆♣

AVAILABLE MODULES

 Start / middle module (SRT/MID)
  End module (END)

LOW OUTPUT | HIGH OUTPUT

- To complete the product add the fixing system. Please order separately.
- For suspended version add the suspension and ceiling rose. Please order separately.
- The luminaire with sensor has 215 mm more than the standard length.
- The maximum number of High-Output luminaires that can be connected in line is 15. With sensor the maximum number is 9.
- The maximum number of Low-Output luminaires that can be connected in line is 35. With sensor the maximum number is 16.

¹ Transparent injected polycarbonate end caps. The product is class II.

² Stainless steel end caps. The product is class I.

³ Only available in dimmable DALI versions. For lengths L620 and L900 mm, Tunable White can only be applied for End line (END) versions.

02. Select options

OPTIONS	Code*
SwitchDIM Tunable White	926600
• The SwitchDIM Tunable White allows the control of up to 20 luminaires.	
Fixing system	
Stainless steel clamp A1 D70 (x2)	915403
Stainless steel clamp A2 D70 (x2)	915405
Stainless steel clamp with fast lock D70 (x2)	915404
Suspension	
S4 L1500 mm (x2)	910200
S4 L3000 mm (x2)	910204
S4 L6000 mm (x2)	910208
Ceiling rose ¹	
Surface mounted T24 D95	978600
Recessed T5 D90	971300
Cable gland for HF versions	
• For all start/middle modules (SRT/MID):	
Metal M16 (x2)	925010
Breathable metal M16 (x2)	926710
• For all end modules (END):	
Metal M16 (x1)	925000
Breathable metal M16 (x1)	926700
Cable gland for DALI versions	
• For all start/middle modules (SRT/MID):	
Metal M20 (x2)	925011
Breathable metal M20 (x2)	926711
• For all end modules (END):	
Metal M20 (x1)	925001
Breathable metal M20 (x1)	926701
Sensor	
• Under request.	
• Detection range: 100%. Hold time: 5s.	
Daylight Threshold: disabled. For other types of programming, consult the sensor's instructions manual.	



*Replace the symbols to complete the code

Colour

<input type="checkbox"/> White	W
<input checked="" type="checkbox"/> Black	B



Product details



