

VEGA /E



Product characteristics

Body
Injected ABS and aluminium heatsink

Finish
Powder coated

Optical system
PRISM+ - Microprismatic diffuser
LIGHT+ - Opal diffuser

Light source
LED, CRI>90, MacAdam Step ≤3

LED lifetime
50.000h @ L90, B10, Ta 25°C


Control gear
Not included

Ceiling thickness
For ceilings between 1-25 mm




01. Select version

VEGA /E




PRISM+ - Microprismatic diffuser



UGR	W	lm output	lm/W	mA	⌀	CODE*
≤19	7	701	100	200	Ø85	90441L0080▲0◆00
≤22	8	856	107	250	Ø85	90441L0110▲0◆00
≤22	12	1152	96	350	Ø85	90441L0150▲0◆00

LIGHT+ - Opal diffuser



UGR	W	lm output	lm/W	mA	⌀	CODE*
≤22	7	649	93	200	Ø85	90430L0080▲0◆00
≤22	8	791	99	250	Ø85	90430L0110▲0◆00
≤22	12	1082	90	350	Ø85	90430L0150▲0◆00



*Replace the symbols to complete the code

Colour	Symbol
White	W
Black	B

Colour temp.	Symbol
3000K	3
4000K	0

VEGA /E

• To complete the product add the control gear. Please order separately.

02. Select options

OPTIONS Code

Control gear HF

Driver 8,4W 10-42V 200mA HF	900001E
Driver 10,5W 10-42V 250mA HF	900002E
Driver 14,7W 10-42V 350mA HF	900004E

Control gear dimmable DALI

Driver 10,4W 09-52V 200mA DALI+ PUSH	900101H
Driver 13W 09-52V 250mA DALI+ PUSH	900102H
Driver 18,2W 09-52V 350mA DALI+ PUSH	900104H

Steel safety cable

L 1500 mm	955010
-----------	--------



Product details



Finish in white colour