

## VEGA IP /E



### Product characteristics

**Body**  
Injected ABS and aluminium heatsink

**Finish**  
Powder coated

**Optical system**  
LIGHT+ - Opal diffuser

**Light source**  
LED, CRI>90, MacAdam Step ≤3

**LED lifetime**  
50.000h @ L90, B10, Ta 25°C


**Control gear**  
Not included

**Ceiling thickness**  
For ceilings between 1-25 mm




## 01. Select version

### VEGA IP / E



#### LIGHT+ - Opal diffuser



W	lm output	lm/W	mA	Ø	CODE*
7	649	93	200	Ø85	90575L0080▲0◆00
8	791	99	250	Ø85	90575L0110▲0◆00
12	1082	90	350	Ø85	90575L0150▲0◆00



\*Replace the symbols to complete the code

Colour	Symbol
White	W
Black	B

Colour temp.	Symbol
3000K	3
4000K	0

### VEGA IP / E

• To complete the product add the control gear. Please order separately.

## 02. Select options

### OPTIONS Code

#### Control gear HF

Driver 8,4W 10-42V 200mA HF	900001E
Driver 10,5W 10-42V 250mA HF	900002E
Driver 14,7W 10-42V 350mA HF	900004E

#### Control gear dimmable DALI

Driver 10,4W 09-52V 200mA DALI+ PUSH	900101H
Driver 13W 09-52V 250mA DALI+ PUSH	900102H
Driver 18,2W 09-52V 350mA DALI+ PUSH	900104H

#### Steel safety cable

L 1500 mm	955010
-----------	--------



### Product details



Finish in white colour