

VEGA Sq /E



Product characteristics

Body
Injected ABS and aluminium heatsink

Finish
Powder coated

Optical system
PRISM+ - Microprismatic diffuser
LIGHT+ - Opal diffuser

Light source
LED, CRI>90, MacAdam Step ≤3

LED lifetime
50.000h @ L90, B10, Ta 25°C


Control gear
Not included

Ceiling thickness
For ceilings between 1-25 mm




01. Select version

VEGA Sq /E




PRISM+ - Microprismatic diffuser



UGR	W	lm output	lm/W	mA	Φ	CODE*
≤19	7	712	102	200	85x85	90442L0080▲0◆00
≤19	8	869	109	250	85x85	90442L0110▲0◆00
≤22	12	1170	98	350	85x85	90442L0150▲0◆00

LIGHT+ - Opal diffuser



UGR	W	lm output	lm/W	mA	Φ	CODE*
≤19	7	701	100	200	85x85	90437L0080▲0◆00
≤22	8	856	107	250	85x85	90437L0110▲0◆00
≤22	12	1152	96	350	85x85	90437L0150▲0◆00

VEGA Sq /E

• To complete the product add the control gear. Please order separately.



*Replace the symbols to complete the code

Colour ▲
 White W
 Black B

Colour temp. ◆
 3000K 3
 4000K 0

02. Select options

OPTIONS Code

Control gear HF

Driver 8,4W 10-42V 200mA HF	900001E
Driver 10,5W 10-42V 250mA HF	900002E
Driver 14,7W 10-42V 350mA HF	900004E

Control gear dimmable DALI

Driver 10,4W 09-52V 200mA DALI+ PUSH	900101H
Driver 13W 09-52V 250mA DALI+ PUSH	900102H
Driver 18,2W 09-52V 350mA DALI+ PUSH	900104H

Steel safety cable

L 1500 mm	955010
-----------	--------



Product details



Finish in white colour