

VEGA Sq



Product characteristics

Body

Aluminium

Finish

Powder coated

Optical system

PRISM+ - Microprismatic diffuser
LIGHT+ - Opal diffuser

Light source

LED, CRI>90, MacAdam Step ≤3

LED lifetime

50.000h @ L90, B10, Ta 25°C

Control gear

LED driver 220-240V-50/60Hz included



230V/50Hz




IP 40

650°C


01. Select version



VEGA Sq




PRISM+ - Microprismatic diffuser



UGR	W	lm output	lm/W	CODE*
≤19	8	743	93	90446L008▼▲0◆00
≤19	9	908	101	90446L011▼▲0◆00
≤22	14	1241	89	90446L015▼▲0◆00

LIGHT+ - Opal diffuser



UGR	W	lm output	lm/W	CODE*
≤22	8	743	93	90444L008▼▲0◆00
≤22	9	921	102	90444L011▼▲0◆00
≤25	14	1259	90	90444L015▼▲0◆00

*Replace the symbols to complete the code

Control gear	
HF	E
DALI	H

Colour	
□ White	W
■ Black	B

Colour temp.	
3000K	3
4000K	0


VEGA Sq

• To complete the product add the current supply cable and the ceiling rose. Please order separately.

02. Select ceiling rose



Recessed




HF

100x100 **CODE***
912720▲

DALI

100x100 **CODE***
912730▲

Surface



HF

100x100 **CODE***
912700▲

DALI

100x100 **CODE***
912710▲

*Replace the symbols to complete the code

Colour	
□ White	W
■ Black	B

CEILING ROSE

• Transparent current supply cable with L1500 mm included.