



LEICA TEMPUS ASPH.

Technical data



Red-dot sight	Leica Tempus ASPH. 3.5 MOA	Leica Tempus ASPH. 2.0 MOA
Order No.	55 500	55 502
Scope of delivery	protection cap, optical cleaning cloth, battery compartment opener, hexagonal key (1.5 mm), two Torx mounting screws (T10)	protection cap, optical cleaning cloth, battery compartment opener, hexagonal key (1.5 mm), two Torx mounting screws (T10)
Front lens (aspherical)	21 x 25 mm	21 x 25 mm
Parallax free	40 m	40 m
Mounting option	Docter Sight	Docter Sight
Adjustment point impact	1.1 MOA per click (approx. 1.6 cm at 50 m)	1.1 MOA per click (approx. 1.6 cm at 50 m)
Adjustment range reticle	100 x 100 MOA (approx. 1.5 m at 50 m)	100 x 100 MOA (approx. 1.5 m at 50 m)
Reticle (red-dot)	3.5 MOA (approx. 5 cm at 50 m)	2.0 MOA (approx. 3 cm at 50 m)
Reticle (red-dot) intensity levels	12 levels	12 levels
Automatic switch-off	after 4 hours	after 4 hours
Powering on	per +/- button	per +/- button
Shooting resistance	1.76 lbs (1 ms) / 800 g (1 ms), not suitable for a pistol	1.76 lbs (1 ms) / 800 g (1 ms), not suitable for a pistol
Waterproof	3 ft. / 1 m depth, 10 minutes	3 ft. / 1 m depth, 10 minutes
Battery	1 x 3 V CR2032 Lithium-type	1 x 3 V CR2032 Lithium-type
Dimensions (L x H x D)	2.1 x 1.35 x 1.1 in / 53.5 x 34.5 x 28 mm	2.1 x 1.35 x 1.1 in / 53.5 x 34.5 x 28 mm
Weight	1.31 oz / 37 g (1.41 oz / 40 g incl. battery)	1.31 oz / 37 g (1.41 oz / 40 g incl. battery)

