



Clean Room FL


Clean Room FL features a special polyester film facing providing excellent ISO clean room performance making it an ideal solution for clean room and computer environments, especially in combination with Zentia Clean Room 24 grid system.

Key Features

- /// ISO 5
- /// Does not attract dust
- /// Adapted to regular washing
- /// Ideal for computer and clean room environments



Edge Detail Board



Thickness (mm) 15

Modules (mm) 600 x 600 9527M
1200 x 600 9529M


Suspension Systems Prelude 24 XL² / TLS
Prelude 24 Corrosive Resistant
Clean Room 24


Colour Global White

Sustainability



39






A+




EN 13964 / E1

Acoustics



EN ISO 354
& EN ISO 11654



EN ISO 21040-9
& EN ISO 717-1


	Hz α_p									
	α_w	D_{nfw}	Class	NRC	125	250	500	1000	2000	4000
Board	0.15	36 dB	E	0.10	0.25	0.15	0.10	0.10	0.15	0.25

Fire Reaction



EEA Euroclass A2-s1, d0
EN 13501-1


Performances & Features




78%




95% RH




ISO 5




ISO 14644-1







30 Year System Guarantee





$\lambda=0.060$
W/m K
EN 12667
& ISO 8301



5.3 Kg/m²







BIM READY

If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on **0800 371 849** or email enquiries@zentia.com