




Hydroboard ($\leq 100\%$ RH)

Hydroboard can resist permanent RH up to 95% and temporary conditions of up to 100% RH. Install with Prelude 24 Corrosive Resistant grid system for higher humidity areas.

Key Features

- Stable at humidity levels of up to 100% RH
- Can be installed in temperatures ranging from 0°C to 40°C
- High acoustic absorption up to 0.95 α_w
- Ideal for WC, shower areas and hydrotherapy rooms. Should be installed on Corrosive Resistant grid



Edge Detail	Board		Tegular		MicroLook 90						
Thickness (mm)	15		15		15						
Modules (mm)	600 x 600 3687M 1200 x 600 3688M		600 x 600 3689M		600 x 600 3691M						
Suspension Systems	Prelude 24 XL ² / TLS Prelude 24 Corrosive Resistant Prelude 24 Sixty ² XL ² / TLS		Prelude 24 XL ² / TLS Prelude 24 Corrosive Resistant Prelude 24 Sixty ² XL ² / TLS		Prelude 15 TL / XL ² Interlude HRC XL ² Silhouette 6mm XL ²						
Colour	Global White										
Sustainability											
	20		A	EN 13964 / E1							
Acoustics											
	EN ISO 354 & EN ISO 11654		EN ISO 10848-2 & EN ISO 717-1								
		α_w	D _{nfw}	Class	NRC	125	250	Hz α_p			
								500	1000	2000	4000
Board		0.95	22 dB	A	0.90	0.35	0.80	1.00	0.85	1.00	1.00
Fire Reaction			A1 EN 13501-1								
Performances & Features		82%		≤100% RH							
		1.2 Kg/m ² Board 2.5 Kg/m ² Tegular 90, MicroLook 90									

While this product is suitable for high humidity environments, it is not suitable to be fitted directly over a swimming pool.

If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on **0800 371 849** or email enquiries@zentia.com

TDS 041.2.08.22