

Processors	Units
DSP-4080A 4 In/8 Out fully configurable DSP, 9 full bandwidth parametric band EQ on each Channel, AudioCore equipped	1

DASnet-Rack	
DASnet-Rack 99 Rack w/ 1 x DASnet-Patch-99 + 1 x DASnet-Patch-PowerCon + 32A power distro	1
USB-485 KK Systems USB to RS-485 convertor	1

Speaker cabling	
eCPK-20 20m CAT7 Integrated etherCON (Data + Audio) + powerCON TRUE1 cable	8
eC-09 0.9m CAT7 etherCON (Data + Audio) link cable	8
Plink1-09 0.9m powerCON TRUE1 link cable	8
eCPK-1 1m CAT7 integrated etherCON (Data + Audio) + powerCON TRUE 1 cable link	4


Rigging frames	
AX-Aero40S3 Rigging Bumper for aero 40A (max 20units)	2

Dollies	
PL-UX218S Caster frame for stacking UX-218/UX-218A (max 3 units)	4
PL-40S Metallic caster frame for stacking aero 40A (max 4 units)	3

Covers	
FUN-4-AERO-40A Black protective transport cover for 4 units of aero 40A on PL-40Saero40	3
FUN-3-UX-218 Black protective transport cover for 3 UX-218/UX-218A on PL-UX218S	4

Truck Configurations	
----------------------	--

Euro truck




243cm / 96"

American Truck 90" x 232"




228cm / 90"

American Truck 99" x 232"



251cm / 99"

DASnet-Rack 99 Connections
----------------------------



DASnet Rack 99