



VxT-20

Module for protection against **transient overvoltages**.

Type 2+3.

DATASHEET






V2T-20




V3T-20

Dimensions




Electrical diagrams

V2T-20



V3T-20





Technical specifications

	V2T-20	V3T-20
GENERALS	Rated voltage Un	230 VAC (L/N)
	Maximum voltage Uc	270 VAC (L/N)
	Frequency	50-60 Hz
	Maximum terminal cross-section	35 mm ²
	Upstream protective fuse	63 A gL
	Environmental limits	-40 ° +80 °C
	Protection	IP20
	Mounting	Rail DIN 35
	Nº of DIN modules	2
	Standards	2014/35/UE (LVD) 2014/30/UE (EMC) 2011/65/UE (RoHS)
	Dimensions (width x height x depth)	18 x 90 x 66 mm
	Average weight approx.	205 g
OVERVOLTAGE	Level protection Up (L/N)	≤1.5 kV
	Level protection Up (N/PE)	≤1.3 kV
	Maximum discharge current (8/20µs) I _{max} (L/N) (N/PE)	20 kA
	Rated discharge current (8/20µs) I _n (L/N) (N/PE)	10 kA
	Combined wave (1,2/50 µs) U _{oc}	10 kV
	Overvoltage response time	≤25 ns
	Type	2+3
	Product standards	IEC/EN 61643-11

Models

V2T-20

Code	Reference
10005100	V2T-20

Scan for more information:



V3T-20

Code	Reference
10005101	V3T-20

Scan for more information:

