




DIMENSIONS



ACCESSORIES



HIGH CHROMATIC LED

	PRODUCT			
Name	SIX S RECESSED 34° 3000K WT			
Reference	A3340131WT			
Color	Textured white			
RAL	9005			
Category	CEILING RECESSED			
	LIGHTING INFORMATION			
Light source	LED			
Gross luminous flux	1070 Lm			
Power	8,5 W			
Power values of the system	9,55 W			
Colour temperature	3000 K			
Colour Rendering Index	CRI>90			
Chromatic stability	Mac Adam Step 2			
Light beam angle	34°			
Lighting efficiency	89%			
Efficacy	126 Lm/W			
Current intensity	500 mA			
Control through bluetooth	Please Consult			
Driver	Included			
Emergency power supply	Please Consult			
Electrical insulation class				
Voltage	220 V/240 V			
Frequency	50/60 Hz			
Energy efficiency	A+			
LED lifespan	L80B10 (Tj=85°C) >60.000h			
	OTHER DATA			
Ingress Protection	IP20			
Recess measurements	Ø50 mm.			
Swivel angle	310°			
Rotation angle	350°			
Weight	277 g.			
Packaged weight	360 g.			
Packaging dimensions	179 × 147 × 71 mm.			
Units per package	1			
Materials	Aluminium / Polycarbonate			



AWARDS






Six Recessed is a spotlight for single recessed lighting solutions that stands out for its elegance and airiness. Its body; disk looking, rounded shaped, encloses an innovative combination of reflector and lens. The combined action of both, allows Six to direct light rays with the maximum uniformity in a very small distance that, at the same time, has made possible its differential design-reduced and minimalist-. In addition, Six can be freely articulated due to its airy arm which allows the spotlight to be orientated in any direction.






POLAR DIAGRAM



CONICAL DIAGRAM



FOR COMMERCIAL PRODUCT SHOWCASING

Vivid Model Colour Temperature	2700K	3000K	3500K	4000K	Light Pink
Reading			•	•	
Fruits & Vegetables		•	•		
⊕ Bakery	•				
2 Retail		•	•		
Cosmetics			•	•	
Q; Meat					•
Fish				•	
Seafood				•	•



For some of its products, Arkoslight offers the possibility to provide them with a special LED, designed to create an illumination focused on visually promoting goods or products for commercial purposes. It is a high chromaticity LED, capable of identifying the colour shades that produce a positive psychological perception of the illuminated object.

This special LED lighting source offers a much more attractive and intense colour range than a conventional LED, besides being much wider. Technically, this is possible thanks to a special LED setting that includes a «special saturation parameter», capable of highlighting the objects colours and materials in such a way that they seem more attractive within the visible light spectrum. To achieve this performance, in each case, the appropriate diode and specific phosphor coating are carefully selected.

