




DIMENSIONS



PRODUCT

Name	DEEP MINI 2 4000K WT
Reference	A2500212WT
Color	Textured white
RAL	9016
Category	CEILING RECESSED

LIGHTING INFORMATION

Light source	LED
Gross luminous flux	1075 Lm
Power	7 W
Power values of the system	7,87 W
Colour temperature	4000 K
Colour Rendering Index	CRI>90
Chromatic stability	Mac Adam Step 2
Light beam angle	89°
Lighting efficiency	76%
Efficacy	154 Lm/W
Current intensity	500 mA
Control through bluetooth	Please Consult
Driver	Included - Connected
Emergency power supply	Please Consult
Electrical insulation class	☐
Voltage	220 V/240 V
Frequency	50/60 Hz
Energy efficiency	A++
LED lifespan	L80B10 (Tc=80°C) >60.000h


OTHER DATA

Ingress Protection	IP43
Impact resistance	IK07
Recess measurements	Ø122 mm.
Weight	650 g.
Packaged weight	786,3 g.
Packaging dimensions	195 x 160 x 90 mm.
Units per package	1
Materials	Aluminium / Polymethyl Methacrylate




Deep is a LED downlight for general lighting functions whose main feature is its attractive aspect, with the diffuser considerably set back with respect to the plane of the perimeter frame.

POLAR DIAGRAM



CONICAL DIAGRAM



UGR

Glare Evaluation According to UGR												
p Ceiling		70	70	50	50	30	70	70	50	50	30	
p Walls		50	30	50	30	30	50	30	50	30	30	
p Floor		20	20	20	20	20	20	20	20	20	20	
Room Size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis					
2H	2H	21.8	22.9	22.0	23.2	23.4	21.8	22.9	22.0	23.2	23.4	
	3H	22.8	23.9	23.1	24.1	24.4	22.8	23.9	23.1	24.1	24.4	
	4H	23.1	24.1	23.4	24.3	24.6	23.1	24.1	23.4	24.3	24.6	
	6H	23.3	24.2	23.6	24.5	24.8	23.3	24.2	23.6	24.5	24.8	
	8H	23.4	24.2	23.7	24.5	24.9	23.4	24.2	23.7	24.5	24.9	
4H	12H	23.4	24.3	23.8	24.6	24.9	23.4	24.3	23.8	24.6	24.9	
	2H	22.1	23.1	22.5	23.4	23.7	22.1	23.1	22.5	23.4	23.7	
	3H	23.3	24.2	23.7	24.5	24.8	23.3	24.2	23.7	24.5	24.8	
	4H	23.7	24.5	24.1	24.8	25.2	23.7	24.5	24.1	24.8	25.2	
	6H	24.0	24.6	24.4	25.0	25.4	24.0	24.6	24.4	25.0	25.4	
8H	8H	24.1	24.7	24.6	25.1	25.5	24.1	24.7	24.6	25.1	25.5	
	12H	24.3	24.8	24.7	25.2	25.6	24.3	24.8	24.7	25.2	25.6	
	4H	23.8	24.4	24.3	24.8	25.2	23.8	24.4	24.3	24.8	25.2	
	6H	24.2	24.7	24.7	25.1	25.6	24.2	24.7	24.7	25.1	25.6	
	8H	24.4	24.8	24.9	25.3	25.8	24.4	24.8	24.9	25.3	25.8	
12H	12H	24.6	25.0	25.1	25.5	26.0	24.6	25.0	25.1	25.5	26.0	
	4H	23.8	24.4	24.3	24.8	25.2	23.8	24.4	24.3	24.8	25.2	
	6H	24.3	24.7	24.7	25.1	25.6	24.3	24.7	24.7	25.1	25.6	
	8H	24.5	24.8	25.0	25.3	25.8	24.5	24.8	25.0	25.3	25.8	
	Variation of the observer position for the luminaire distances S											
S = 1.0H S = 1.5H S = 2.0H		+0.2 / -0.3 +0.4 / -0.8 +1.0 / -1.5					+0.2 / -0.3 +0.4 / -0.8 +1.0 / -1.5					
Standard table		BK03					BK03					
Correction Summand		5.8					5.8					
Corrected Glare Indices referring to 1075lm Total Luminous Flux												