




DIMENSIONS



ACCESSORIES



LARK 111

PRODUCT

Name	ORBITAL TRIMLESS 2 LARK111 W
Reference	A0101203W
Color	Matt white
RAL	9016
Category	CEILING RECESSED

LIGHTING INFORMATION

Light source	LARK 111 EXCL
Power	Max 2 x 12 W
Power values of the system	NA W
Chromatic stability	Mac Adam Step 2
Control through bluetooth	Please Consult
Driver	Excluded
Emergency power supply	Please Consult
Electrical insulation class	
Voltage	220 V/240 V
Frequency	50/60 Hz
Energy efficiency	A-A++
LED lifespan	L80B10 (Tj=85°C) >60.000h

OTHER DATA

Ingress Protection	IP20
Recess measurements	166 x 306 mm.
Swivel angle	X35° Y35°
Weight	2000 g.
Packaged weight	2177,4 g.
Packaging dimensions	330 x 190 x 120 mm.
Units per package	1
Materials	Aluminium



Combine the colours of the inner structure and lamp fixation elements of Orbital Trimless with the finishes of our LARK- 111 LED lamps and achieve a recessed cardan fixture that will perfectly form part of the interior design of your residential property, business, hotel or gastronomy Project.



LarK-111



LarK-111 · HONEYCOMB LOUVER



reddot design award
winner 2014



LarK-111					P	CCT	Beam	I	Flux	Flux Out	LOR
 PHASE CUT *	A25	⊗	-10-10-	W N Z	6,5W	2700K	19°	200mA	900Lm	828Lm	92%
	A25	⊗	-10-11-	W N Z	6,5W	3000K	19°	200mA	940Lm	865Lm	92%
	A25	⊗	-10-12-	W N Z	6,5W	4000K	19°	200mA	950Lm	874Lm	92%
	A25	⊗	-10-20-	W N Z	6,5W	2700K	40°	200mA	900Lm	774Lm	86%
	A25	⊗	-10-21-	W N Z	6,5W	3000K	40°	200mA	940Lm	808Lm	86%
	A25	⊗	-10-22-	W N Z	6,5W	4000K	40°	200mA	950Lm	817Lm	86%
	A25	⊗	-20-10-	W N Z	12W	2700K	19°	350mA	1440Lm	1325Lm	92%
	A25	⊗	-20-11-	W N Z	12W	3000K	19°	350mA	1500Lm	1380Lm	92%
	A25	⊗	-20-12-	W N Z	12W	4000K	19°	350mA	1520Lm	1398Lm	92%
	A25	⊗	-20-20-	W N Z	12W	2700K	40°	350mA	1440Lm	1238Lm	86%
 PHASE CUT *	A25	⊗	-20-21-	W N Z	12W	3000K	40°	350mA	1500Lm	1290Lm	86%
	A25	⊗	-20-22-	W N Z	12W	4000K	40°	350mA	1520Lm	1307Lm	86%
	A25	⊗	-21-10-	W N Z	12W	2700K	19°	350mA	1440Lm	1325Lm	92%
	A25	⊗	-21-11-	W N Z	12W	3000K	19°	350mA	1500Lm	1380Lm	92%
 DALI PUSH *	A25	⊗	-21-12-	W N Z	12W	4000K	19°	350mA	1520Lm	1398Lm	92%
	A25	⊗	-21-20-	W N Z	12W	2700K	40°	350mA	1440Lm	1238Lm	86%
	A25	⊗	-21-21-	W N Z	12W	3000K	40°	350mA	1500Lm	1290Lm	86%
	A25	⊗	-21-22-	W N Z	12W	4000K	40°	350mA	1520Lm	1307Lm	86%
	A25	⊗	-21-22-	W N Z	12W	4000K	40°	350mA	1520Lm	1307Lm	86%



220
240V~



CRI>90 | L80B10
> 60.000h




⊗ OPTIONS


2	LarK-111
3	LarK-111 Honeycomb**

* OTHER DIM OPTIONS PLEASE CONSULT | ** Honeycomb affects lighting parameters

LarK-111



LarK-111 · HONEYCOMB LOUVER



COLOUR | W □ RAL 9016 | N ■ RAL 9005 | Z ■ RAL 9006 |

MATERIAL | AL |

& » PLEASE CONSULT

Calle N · Pol. Ind. EL OLIVERAL
46394 Ribarroja del Turia · Valencia (Spain)
Tel. +34 961 667 207 · Fax +34 961 667 054
info@arkoslight.com · www.arkoslight.com

