




DIMENSIONS



ACCESSORIES



LARK

PRODUCT

Name	ORBITAL MINI 2 LARK W
Reference	A1962100W
Color	Matt white
RAL	9016
Category	CEILING RECESSED

LIGHTING INFORMATION

Light source	LARK EXCL
Power	Max 2 x 7,5 W
Power values of the system	NA W
Control through bluetooth	Please Consult
Driver	Excluded
Emergency power supply	Please Consult
Electrical insulation class	
Voltage	220 V/240 V
Energy efficiency	A++
LED lifespan	L80B10 (Tj=85°C) >60.000h

OTHER DATA

Ingress Protection	IP20
Recess measurements	113 x 204 mm.
Swivel angle	X30° Y30°
Weight	1030 g.
Packaged weight	1195 g.
Packaging dimensions	251 x 154 x 154 mm.
Units per package	1
Materials	Aluminium



Orbital Mini is a ceiling recessed luminaire whose beam can be directed in an angle of up to 30 degrees per axis. Versatile, functional and -due to its small size- very discrete and elegant.



		P	CCT	I	Flux	Flux Out	LOR
LARK	0434-00-96	5W	2700K	140mA	700Lm	644Lm	92%
	0434-00-05	5W	3000K	140mA	730Lm	672Lm	92%
	0434-00-19	5W	4000K	140mA	750Lm	690Lm	92%
	0434-01-02	7,5W	2700K	200mA	950Lm	874Lm	92%
	0434-00-09	7,5W	3000K	200mA	1000Lm	920Lm	92%
	0434-00-17	7,5W	4000K	200mA	1030Lm	948Lm	92%
 PHASE CUT *	0434-01-03	7,5W	2700K	200mA	950Lm	874Lm	92%
	0434-00-15	7,5W	3000K	200mA	1000Lm	920Lm	92%
	0434-00-18	7,5W	4000K	200mA	1030Lm	948Lm	92%
 DALI PUSH *	0434-01-04	7,5W	2700K	200mA	950Lm	874Lm	92%
	0434-01-05	7,5W	3000K	200mA	1000Lm	920Lm	92%
	0434-01-06	7,5W	4000K	200mA	1030Lm	948Lm	92%

 | 220-240 V~ |  CRI>80 | > 60.000 h L90B10


 MacAdam Step 2

 INCL

 FAST | CONNEC

 38°

Lark



* OTHER DIM OPTIONS PLEASE CONSULT

 &  » PLEASE CONSULT