




DIMENSIONS



ACCESSORIES







ADD-ON BEZEL

Reference	A2162220W
Color	Matt white
RAL	Colour in the mass looks alike RAL 9010
Category	CEILING RECESSED
	LIGHTING INFORMATION
Light source	LED
Gross luminous flux	910 Lm
Power	7 W
Power values of the system	9,33 W
Colour temperature	2700 K
Colour Rendering Index	CRI>90
Chromatic stability	Mac Adam Step 2
Light beam angle	45°
Lighting efficiency	86%
Efficacy	130 Lm/W
Current intensity	200 mA
Dimming	Phase Cut - Other DIM, please consult
Control through bluetooth	Please Consult
Driver	Included - Fast Connect
Emergency power supply	Please Consult
Electrical insulation class	
Voltage	220 V/240 V
Frequency	50/60 Hz
Energy efficiency	A+
LED lifespan	L80B10 (Tj=85°C) >60.000h
	OTHER DATA
Ingress Protection	IP20
Impact resistance	IK07
Recess measurements	Ø75 mm.

PRODUCT

Name

SWAP ASYM M 7W DIM PH.CUT 2700K W



215 g.

256 g.

99 × 102 × 107 mm.

Weight

Materials

Packaged weight

Packaging dimensions
Units per package

04-07-19 / 20:21



Aluminium / Polycarbonate

AWARDS






Swap is a ceiling recessed LED spotlight whose main features are its minimalist aspect, its perfect integration into the ceiling, and considerable visual comfort, thanks to the small reflector that is set back with respect to the ceiling plane. When it is switched on, its matte finish shade generates an attractive effect, a discrete circle of light. It includes an add-on bezel that can be used optionally to cover larger recess diameters.






POLAR DIAGRAM




CONICAL DIAGRAM









Ī	Model
_,	Reference
_	Category

PRODUCT

IP54 Accessory M

A2122054 Accessories

PRE-ASSEMBLED. NOT SOLD SEPARATELY.
AFFECTS THE LIGHTING PARAMETERS.



To make the difference, Swap IP54 reaches a high sealing level, maintaining at the same time the same aesthetics as a standard Swap. The insulating property is obtained thanks to a protection placed just over the LED, and a silicone joint on the internal part of the bezel. In this way, the external aspect of Swap IP54 is identical to any other Swap IP20.

Swap offers the possibility of requesting any of its models with IP54-rated weather resistance, which converts it into an optimal luminaire to be installed in atmospheres where the product may suffer from the impact of water or frequent presence of humidity.







PRODUCT
Swap M Asymmetric Add-On Bezel
W □ Matt white
Accessories



Accessory always included but for optional use.

It extends the piece's bezel to cover larger recesses, keeping Swap's minimalism and its perfect integration into the ceiling.

Easy to fit. Ideal for reforms to replace the light spot, with the already existing holes, without altering the ceiling or repainting. Swap is the best option for updating to LED technology by means of a real light fixture with incorporated LED, in contrast to just a retrofit lamp that only implies a less efficient update of the light source.

