


SWAP ASYM L 7W DIM DALI/PUSH 3000K W



## DIMENSIONS



## ACCESSORIES







ADD-ON BEZEL

Indille	SWAF ASTM E /W DIM DALI/FUSH SUUUN W
Reference	A2163231W
Color	Matt white
RAL	Colour in the mass looks alike RAL 9010
Category	CEILING RECESSED
	LIGHTING INFORMATION
Light source	LED
Gross luminous flux	940 Lm
Power	7 W
Power values of the system	7,95 W
Colour temperature	3000 K
Colour Rendering Index	CRI>90
Chromatic stability	Mac Adam Step 2
Light beam angle	43°
Lighting efficiency	86%
Efficacy	134 Lm/W
Current intensity	200 mA
Dimming	DALI / Push - Other DIM, please consult
Control through bluetooth	Please Consult
Driver	Included - Fast Connect
Emergency power supply	Please Consult
Electrical insulation class	
Voltage	220 V/240 V
Frequency	50/60 Hz
Energy efficiency	A++
LED lifespan	L80B10 (Tj=85°C) >60.000h
	OTHER DATA
Ingress Protection	IP20
Impact resistance	IK07
Recess measurements	Ø85 mm.
Weight	240 g.
Packaged weight	288,5 g.

PRODUCT

Name



Packaging dimensions

Units per package

Materials



Aluminium / Polycarbonate

147 × 132 × 134 mm.

AWARDS






Swap is a ceiling recessed LED spotlight whose main features are its minimalist aspect, its perfect integration into the ceiling, and considerable visual comfort, thanks to the small reflector that is set back with respect to the ceiling plane. When it is switched on, its matte finish shade generates an attractive effect, a discrete circle of light. It includes an add-on bezel that can be used optionally to cover larger recess diameters.






## POLAR DIAGRAM




## CONICAL DIAGRAM









	PRODUCT	
Model	IP54 Accessory L	
Reference	A2123054	
Category	Accessories	
	PRE-ASSEMBLED. NOT SOLD SEPARATELY.	7

To make the difference, Swap IP54 reaches a high sealing level, maintaining at the same time the same aesthetics as a standard Swap. The insulating property is obtained thanks to a protection placed just over the LED, and a silicone joint on the internal part of the bezel. In this way, the external aspect of Swap IP54 is identical to any other Swap IP20.

Swap offers the possibility of requesting any of its models with IP54-rated weather resistance, which converts it into an optimal luminaire to be installed in atmospheres where the product may suffer from the impact of water or frequent presence of humidity.







	PRODUCT
Model	Swap L Asymmetric Add-On Bezel
Colour	W □   Matt white
Category	Accessories



Accessory always included but for optional use.

It extends the piece's bezel to cover larger recesses, keeping Swap's minimalism and its perfect integration into the ceiling.

Easy to fit. Ideal for reforms to replace the light spot, with the already existing holes, without altering the ceiling or repainting. Swap is the best option for updating to LED technology by means of a real light fixture with incorporated LED, in contrast to just a retrofit lamp that only implies a less efficient update of the light source.

