




DIMENSIONS



ACCESSORIES



DRIVER OPTIONS

PRODUCT

Name	DARK 40° 2700K NX
Reference	A2740020NX
Color	Stainless steel
Category	WALL & FLOOR LIGHTS

LIGHTING INFORMATION


Light source	LED
Gross luminous flux	100 / 180 / 250 Lm
Power	1 / 2,1 / 3,2 W
Colour temperature	2700 K
Colour Rendering Index	CRI>90
Chromatic stability	Mac Adam Step 3
Light beam angle	40°
Lighting efficiency	83%
Efficacy	110 Lm/W
Current intensity	350 / 700 / 1050 mA
Dimming	No Dim - Other DIM, please consult
Control through bluetooth	Please Consult
Driver	Excluded
Electrical insulation class	III
Energy efficiency	A++
LED lifespan	L80B10 (Tc=85°C) >60.000h

OTHER DATA

Ingress Protection	IP65
Impact resistance	IK08
Recess measurements	Ø52 mm.
Outdoor Use	Yes
Maximum surface temperature	40°
Supported load	5000 N.
Weight	235 g.
Packaged weight	266,4 g.
Packaging dimensions	82 x 74 x 91 mm.
Units per package	1
Materials	Stainless Steel / Aluminium / Glass-Transparent



Dark is a floor-recessed LED luminaire used together with elements that we wish to illuminate upwards, to be able to highlight their architectonic presence (structures, walls, trees, gardens, cornices, etc.). *** NOTE: Recessed box included



DRIVER OPTIONS*	P	I	
0434-00-39	1W	350mA	1 to 12 Darks
0434-00-40	2,1W	700mA	1 to 12 Darks
0434-00-41	3,2W	1050mA	1 to 11 Darks

*Higher IP & DIM Drivers please consult

 NO DIM | IP20