


DIMENSIONS




Name	FIFTY RECESSED 120 4000K NT
Reference	A2310212NT
Color	Textured black
RAL	9016
Category	CEILING RECESSED
<b>PRODUCT</b>	
Light source	LED
Gross luminous flux	3000 Lm
Power	20,4 W
Power values of the system	24,00 W
Colour temperature	4000 K
Colour Rendering Index	CRI>90
Chromatic stability	Mac Adam Step 2
Light beam angle	102°
Lighting efficiency	70%
Efficacy	147 Lm/W
Current intensity	600 mA
Control through bluetooth	Please Consult
Driver	Included
Electrical insulation class	⊕
Voltage	220 V/240 V
Frequency	50/60 Hz
Energy efficiency	A+
LED lifespan	L80B10 (Tc=80°C) >60.000h
<b>LIGHTING INFORMATION</b>	
Ingress Protection	IP20
Recess measurements	1148 × 58 mm.
Diffuser included	Yes
Weight	4730 g.
Packaged weight	6440 g.
Packaging dimensions	Ø168 × 1305 mm.
Units per package	1
Materials	Aluminium / Polycarbonate
<b>OTHER DATA</b>	



Fifty is the recessed LED profile of Arkoslight. Fifty, also available in trimless version, it's ideal for longitudinal lighting solutions, where its diffuser contributes to light up in a functional way. On the whole, this profile is capable of assuming the task of highlighting the different lines, volumes or lanes which are defined in the architecture of spaces.

POLAR DIAGRAM



CONICAL DIAGRAM

