




DIMENSIONS



PRODUCT	
Name	FIFTY SURFACE 300 3000K NT
Reference	A2320411NT
Color	Textured black
RAL	9005
Category	SURFACE
LIGHTING INFORMATION	
Light source	LED
Gross luminous flux	7300 Lm
Power	51 W
Power values of the system	60,00 W
Colour temperature	3000 K
Colour Rendering Index	CRI>90
Chromatic stability	Mac Adam Step 2
Light beam angle	102°
Lighting efficiency	70%
Efficacy	143 Lm/W
Current intensity	600 mA
Control through bluetooth	Please Consult
Driver	Included
Electrical insulation class	⊕
Voltage	220 V/240 V
Frequency	50/60 Hz
Energy efficiency	A+
LED lifespan	L80B10 (Tc=80°C) >60.000h
OTHER DATA	
Ingress Protection	IP20
Diffuser included	Yes
Weight	11830 g.
Packaged weight	13786 g.
Packaging dimensions	Ø128 × 1570 mm.
Units per package	1
Materials	Aluminium / Polycarbonate



Fifty Surface, is the LED profile for surface applications; ideal for longitudinal lighting solutions, where its diffuser contributes to light up in a functional way. On the whole, this profile is capable of assuming the task of highlighting the different lines, volumes or lanes which are defined in the architecture of spaces.

POLAR DIAGRAM



CONICAL DIAGRAM

