




DIMENSIONS



ACCESSORIES



CUSTOM ACCESSORIES

PRODUCT

Name	FIFTY WALL CUSTOM 90 3000K WT
Reference	A2341111WT
Color	Textured white
RAL	9016
Category	CUSTOM SYSTEMS

LIGHTING INFORMATION

Light source	LED
Gross luminous flux	2190 Lm
Power	15,3 W
Power values of the system	18,00 W
Colour temperature	3000 K
Colour Rendering Index	CRI>90
Chromatic stability	MacAdam Step 2
Light beam angle	102°
Lighting efficiency	70%
Efficacy	143 Lm/W
Current intensity	600 mA
Control through bluetooth	Please Consult
Driver	Included - Fast Connect
Electrical insulation class	⌚
Voltage	220 V/240 V
Frequency	50/60 Hz
Energy efficiency	A+
LED lifespan	L80B10 (Tc=80°C) >60.000h


OTHER DATA

Ingress Protection	IP20
Diffuser included	Yes
Weight	3550 g.
Packaged weight	4620 g.
Packaging dimensions	Ø128 × 1000 mm
Units per package	1
Materials	Aluminium / Polycarbonate




Fifty Custom, is Arkoslight's profile solution for surface, recessed, suspension or wall applications for lighting projects where a very specific length is required. A tailored suit.

POLAR DIAGRAM



CONICAL DIAGRAM




FIFTY 2 End Cap Kit	1050-00-10- WT NT
----------------------------	-----------------------



FIFTY Straight Joiner	1050-01-80
------------------------------	------------



FIFTY Power Line	A234-00-00
-------------------------	------------



COLOUR | WT ☐ RAL 9016 | NT ☒ RAL 9005 |

MATERIAL | ☒ AL |