




DIMENSIONS



ACCESSORIES



CUSTOM ACCESSORIES

PRODUCT

Name	FIFTY WALL CUSTOM 90 DIM DALI/PUSH 4000K WT
Reference	A2341122WT
Color	Textured white
RAL	9016
Category	CUSTOM SYSTEMS

LIGHTING INFORMATION

Light source	LED
Gross luminous flux	2250 Lm
Power	15,3 W
Power values of the system	17,39 W
Colour temperature	4000 K
Colour Rendering Index	CRI>90
Chromatic stability	MacAdam Step 2
Light beam angle	102°
Lighting efficiency	70%
Efficacy	147 Lm/W
Current intensity	600 mA
Dimming	DALI / Push
Control through bluetooth	Please Consult
Driver	Included - Fast Connect
Electrical insulation class	⊕
Voltage	220 V/240 V
Frequency	50/60 Hz
Energy efficiency	A+
LED lifespan	L80B10 (Tc=80°C) >60.000h


OTHER DATA

Ingress Protection	IP20
Diffuser included	Yes
Weight	3550 g.
Packaged weight	4620 g.
Packaging dimensions	Ø128 × 1285 mm
Units per package	1
Materials	Aluminium / Polycarbonate




Fifty Custom, is Arkoslight's profile solution for surface, recessed, suspension or wall applications for lighting projects where a very specific length is required. A tailored suit.

POLAR DIAGRAM



CONICAL DIAGRAM




FIFTY 2 End Cap Kit	1050-00-10- WT NT
----------------------------	-----------------------



FIFTY Straight Joiner	1050-01-80
------------------------------	------------



FIFTY Power Line	A234-00-00
-------------------------	------------



COLOUR | WT ☐ RAL 9016 | NT ☒ RAL 9005 |

MATERIAL |  AL |