




### DIMENSIONS



# ACCESSORIES







ADD-ON BEZEL

_	Г	ιυ	ν	U	_		
- 0	) E	'n	n	П	$\cap$	т	

Name

Color RAL

Reference

M M SUPERCRI 7W DIM DALI/PUSH 2700K W

A3162230W

Matt white

Colour in the mass looks alike RAL 9010

CEILING RECESSED Category

Light source
Gross luminous flux
Power
Power values of the system
Colour temperature

Colour temperature
Colour Rendering Index
Chromatic stability

om om and otability
Light beam angle
Lighting efficiency
Efficacy

Current intensity	
Dimming	

	Driver
Emergency power	supply

Control through bluetooth

Electrical insulation class

	Voltage
	Frequency
_	

Energy efficiency
LED lifespan

Materials

## LIGHTING INFORMATION

LED
770 Lm
7 W
9,33 W
2700 K
CRI>97

Mac Adam Step 2	
45°	

86%
110 Lm/W
200 mA

DALI / Push - Other DIM, please consult
Please Consult

Included - Fast Connect	
Please Consult	

220 V/240 V	
50/60 Hz	

A+	
L80B10 (Tj=85°C) >60.000h	

OTHER DATA		

Ingress Protection	IP20
Impact resistance	IK07
Recess measurements	Ø75 mm.
Weight	215 g.

Packaged weight	256 g.
Packaging dimensions	147 × 132 × 134 mm.
Units per package	1

Aluminium / Polycarbonate





AWARDS






Swap is a ceiling recessed LED spotlight whose main features are its minimalist aspect, its perfect integration into the ceiling, and considerable visual comfort, thanks to the small reflector that is set back with respect to the  $\frac{1}{2}$  $ceiling \ plane. \ When \ it is \ switched \ on, its \ matte \ finish \ shade \ generates \ an \ attractive \ effect, a \ discrete \ circle \ of \ light.$ It includes an add-on bezel that can be used optionally to cover larger recess diameters.






# POLAR DIAGRAM




# CONICAL DIAGRAM









Ī	Model
_,	Reference
_	Category

PRODUCT

IP54 Accessory M

A2122054 Accessories

PRE-ASSEMBLED. NOT SOLD SEPARATELY.
AFFECTS THE LIGHTING PARAMETERS.



To make the difference, Swap IP54 reaches a high sealing level, maintaining at the same time the same aesthetics as a standard Swap. The insulating property is obtained thanks to a protection placed just over the LED, and a silicone joint on the internal part of the bezel. In this way, the external aspect of Swap IP54 is identical to any other Swap IP20.

Swap offers the possibility of requesting any of its models with IP54-rated weather resistance, which converts it into an optimal luminaire to be installed in atmospheres where the product may suffer from the impact of water or frequent presence of humidity.







PRODUCT
Swap M Asymmetric Add-On Bezel
W □   Matt white
Accessories



Accessory always included but for optional use.

It extends the piece's bezel to cover larger recesses, keeping Swap's minimalism and its perfect integration into the ceiling.

Easy to fit. Ideal for reforms to replace the light spot, with the already existing holes, without altering the ceiling or repainting. Swap is the best option for updating to LED technology by means of a real light fixture with incorporated LED, in contrast to just a retrofit lamp that only implies a less efficient update of the light source.

