


DIMENSIONS



ACCESSORIES



CUSTOM ACCESSORIES

| | |
|-----------|------------------------------------|
| Name | FIFTY RECESSED CUSTOM 300 4000K NT |
| Reference | A2311412NT |
| Color | Textured black |
| RAL | 9005 |
| Category | CUSTOM SYSTEMS |

PRODUCT

FIFTY RECESSED CUSTOM 300 4000K NT
A2311412NT
Textured black
9005
CUSTOM SYSTEMS

LIGHTING INFORMATION

| | |
|-----------------------------|---------------------------|
| Light source | LED |
| Gross luminous flux | 7500 Lm |
| Power | 51 W |
| Power values of the system | 60,00 W |
| Colour temperature | 4000 K |
| Colour Rendering Index | CRI>90 |
| Chromatic stability | MacAdam Step 2 |
| Light beam angle | 102° |
| Lighting efficiency | 70% |
| Efficacy | 147 Lm/W |
| Current intensity | 600 mA |
| Control through bluetooth | Please Consult |
| Driver | Included - Fast Connect |
| Electrical insulation class | ⊕ |
| Voltage | 220 V/240 V |
| Frequency | 50/60 Hz |
| Energy efficiency | A+ |
| LED lifespan | L80B10 (Tc=80°C) >60.000h |


OTHER DATA

| | |
|----------------------|---------------------------|
| Ingress Protection | IP20 |
| Recess measurements | 2852 × 58 mm. |
| Diffuser included | Yes |
| Weight | 11830 g. |
| Packaged weight | 16230 g. |
| Packaging dimensions | Ø168 × 3005 mm |
| Units per package | 1 |
| Materials | Aluminium / Polycarbonate |




Fifty Custom, is Arkoslight's profile solution for surface, recessed, suspension or wall applications for lighting projects where a very specific length is required. A tailored suit.



POLAR DIAGRAM



CONICAL DIAGRAM



| | |
|------------------------------|-----------------------|
| FIFTY 2 End Cap Kit Recessed | 1050-00-20- WT NT |
| FIFTY Straight Joiner | 1050-01-80 |
| FIFTY Power Line | A231-00-00 |



COLOUR | WT □ RAL 9016 | NT ■ RAL 9005 |

MATERIAL |  AL |