




DIMENSIONS



ACCESSORIES



CUSTOM ACCESSORIES

Name	FIFTY SURFACE CUSTOM 150 3000K NT
Reference	A2321311NT
Color	Textured black
RAL	9005
Category	CUSTOM SYSTEMS

PRODUCT

Light source	LED
Gross luminous flux	3650 Lm
Power	25,5 W
Power values of the system	30,00 W
Colour temperature	3000 K
Colour Rendering Index	CRI>90
Chromatic stability	MacAdam Step 2
Light beam angle	102°
Lighting efficiency	70%
Efficacy	143 Lm/W
Current intensity	600 mA
Control through bluetooth	Please Consult
Driver	Included - Fast Connect
Electrical insulation class	Ⓜ
Voltage	220 V/240 V
Frequency	50/60 Hz
Energy efficiency	A+
LED lifespan	L80B10 (Tc=80°C) >60.000h

LIGHTING INFORMATION


Ingress Protection	IP20
Diffuser included	Yes
Weight	5920 g.
Packaged weight	7635 g.
Packaging dimensions	Ø128 × 1000 mm
Units per package	1
Materials	Aluminium / Polycarbonate

OTHER DATA




Fifty Custom, is Arkoslight's profile solution for surface, recessed, suspension or wall applications for lighting projects where a very specific length is required. A tailored suit.


POLAR DIAGRAM



CONICAL DIAGRAM



FIFTY 2 End Cap Kit	1050-00-10-   WT   NT
FIFTY Straight Joiner	1050-01-80
FIFTY Power Line	A231-00-00



COLOUR | WT □ RAL 9016 | NT ■ RAL 9005 |

MATERIAL |  AL |