



LarK-111



LarK-111 · HONEYCOMB LOUVER

Lark-111						P	CCT	Beam	I	Flux	Flux Out	LOR
PHASE CUT *	A25	⊗	-10-10-	W N	6,5W	2700K	19°	200mA	900 lm	828 lm	92%	
	A25	⊗	-10-11-	W N	6,5W	3000K	19°	200mA	940 lm	865 lm	92%	
	A25	⊗	-10-12-	W N	6,5W	4000K	19°	200mA	950 lm	874 lm	92%	
	A25	⊗	-10-20-	W N	6,5W	2700K	40°	200mA	900 lm	774 lm	86%	
	A25	⊗	-10-21-	W N	6,5W	3000K	40°	200mA	940 lm	808 lm	86%	
	A25	⊗	-10-22-	W N	6,5W	4000K	40°	200mA	950 lm	817 lm	86%	
PHASE CUT *	A25	⊗	-20-10-	W N	12W	2700K	19°	350mA	1440 lm	1325 lm	92%	
	A25	⊗	-20-11-	W N	12W	3000K	19°	350mA	1500 lm	1380 lm	92%	
	A25	⊗	-20-12-	W N	12W	4000K	19°	350mA	1520 lm	1398 lm	92%	
	A25	⊗	-20-20-	W N	12W	2700K	40°	350mA	1440 lm	1238 lm	86%	
	A25	⊗	-20-21-	W N	12W	3000K	40°	350mA	1500 lm	1290 lm	86%	
	A25	⊗	-20-22-	W N	12W	4000K	40°	350mA	1520 lm	1307 lm	86%	
DALI I PUSH *	A25	⊗	-21-10-	W N	12W	2700K	19°	350mA	1440 lm	1325 lm	92%	
	A25	⊗	-21-11-	W N	12W	3000K	19°	350mA	1500 lm	1380 lm	92%	
	A25	⊗	-21-12-	W N	12W	4000K	19°	350mA	1520 lm	1398 lm	92%	
	A25	⊗	-21-20-	W N	12W	2700K	40°	350mA	1440 lm	1238 lm	86%	
	A25	⊗	-21-21-	W N	12W	3000K	40°	350mA	1500 lm	1290 lm	86%	
	A25	⊗	-21-22-	W N	12W	4000K	40°	350mA	1520 lm	1307 lm	86%	

220 V~ | CRI>90 | L90B10 >55.000h

* OTHER DIM options PLEASE CONSULT



⊗ OPTIONS

2	LarK-111
3	LarK-111 Honeycomb**

** Honeycomb affects lighting parameters

