




DIMENSIONS



AWARDS




PRODUCT	
Name	BLACK FOSTER SURF 10 FLOOD 2700K NT
Reference	A3205010NT
Color	Textured black
RAL	9005
Category	SURFACE
LIGHTING INFORMATION	
Light source	LED
Gross luminous flux	1900 Lm
Power	21 W
Power values of the system	23,86 W
Colour temperature	2700 K
Colour Rendering Index	CRI>90
Chromatic stability	MacAdam Step 3
Light beam angle	38°
Lighting efficiency	92%
Efficacy	90 Lm/W
Current intensity	700 mA
Control through bluetooth	Please Consult
Driver	Included
Electrical insulation class	
Voltage	220 V/240 V
Frequency	50/60 Hz
Energy efficiency	A
LED lifespan	L80B10 (Tc=85°C) >60.000h
OTHER DATA	
Ingress Protection	IP20
Weight	1340 g.
Packaged weight	1950 g.
Packaging dimensions	D128 x 480 mm
Units per package	1
Materials	Aluminium / Acrylonitrile Butadiene Styrene / Polycarbonate




Black Foster Surface is the product that transfers the claimed effect "The Invisible Black" to a linear system in surface application. Black Foster has a very discrete presence in the interior design due to its reduced dimensions and its extremely low glare helping the piece not to gain much prominence.

POLAR DIAGRAM



CONICAL DIAGRAM



UGR

Glare Evaluation According to UGR											
ρ Ceiling		70	70	50	50	30	70	70	50	50	30
ρ Walls		50	30	50	30	30	50	30	50	30	30
ρ Floor		20	20	20	20	20	20	20	20	20	20
Room Size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	-13.9	-13.3	-13.7	-13.1	-12.9	-14.7	-14.1	-14.5	-13.9	-13.7
	3H	-7.6	-7.0	-7.3	-6.8	-6.6	-7.5	-6.9	-7.2	-6.6	-6.4
	4H	-4.1	-3.5	-3.8	-3.3	-3.0	-3.5	-3.0	-3.2	-2.7	-2.5
	6H	-0.4	0.1	-0.1	0.3	0.6	-0.1	0.4	0.3	0.7	1.0
	8H	1.4	1.9	1.7	2.2	2.5	1.7	2.2	2.1	2.5	2.8
4H	12H	3.4	3.9	3.7	4.2	4.5	3.8	4.2	4.1	4.5	4.8
	2H	-11.3	-10.8	-11.0	-10.5	-10.3	-11.7	-11.1	-11.4	-10.9	-10.6
	3H	-5.4	-4.9	-5.0	-4.6	-4.3	-5.2	-4.7	-4.8	-4.4	-4.1
	4H	-1.9	-1.5	-1.6	-1.2	-0.9	-1.5	-1.1	-1.1	-0.8	-0.4
	6H	1.6	1.9	2.0	2.3	2.7	1.9	2.3	2.3	2.6	3.0
8H	8H	3.5	3.8	3.9	4.2	4.6	3.8	4.1	4.2	4.4	4.8
	12H	5.5	5.8	6.0	6.2	6.6	5.9	6.1	6.3	6.5	6.9
	4H	-0.4	-0.1	0.0	0.3	0.7	-0.1	0.2	0.3	0.6	1.0
	6H	3.2	3.5	3.7	3.9	4.3	3.5	3.7	3.9	4.1	4.5
	8H	5.2	5.4	5.7	5.8	6.3	5.4	5.6	5.9	6.0	6.5
12H	12H	7.4	7.5	7.9	8.0	8.5	7.6	7.8	8.1	8.2	8.7
	4H	0.1	0.4	0.6	0.8	1.2	0.4	0.6	0.8	1.0	1.4
	6H	3.8	4.0	4.3	4.5	4.9	4.0	4.2	4.5	4.6	5.1
	8H	5.9	6.0	6.4	6.5	7.0	6.1	6.2	6.6	6.7	7.2
Variation of the observer position for the luminaire distances S											
S = 1.0H		+0.9 / -0.3					+1.3 / -0.4				
S = 1.5H		+1.9 / -0.6					+2.7 / -0.7				
S = 2.0H		+3.1 / -0.8					+4.2 / -1.0				
Standard table		---					---				
Correction		---					---				
Summand		---					---				
Corrected Glare Indices referring to 1900lm Total Luminous Flux											