




## DIMENSIONS



## ACCESSORIES



ANTI-GLARE HONEYCOMB LOUVER



TRACK 48V OPTIONS

Name	FIT 35 48V DIM DALI 38° 2700K NT
Reference	A3450230NT
Color	Textured black
RAL	9005
Category	TRACKLIGHTS

## PRODUCT

## LIGHTING INFORMATION

Light source	LED
Gross luminous flux	590 Lm
Power	5,5 W
Power values of the system	5,79 W
Colour temperature	2700 K
Colour Rendering Index	CRI>90
Chromatic stability	MacAdam Step 2
Light beam angle	38°
Lighting efficiency	80%
Efficacy	107 Lm/W
Current intensity	500 mA
Dimming	DALI
Control through bluetooth	Please Consult
Driver	Included
Electrical insulation class	III
Voltage	48 Vdc
Energy efficiency	A+
LED lifespan	L80B10 (Tj=85°C) >60.000h


## OTHER DATA

Ingress Protection	IP20
Swivel angle	90°
Rotation angle	360°
Track type	Track 48V
Weight	180 g.
Packaged weight	250 g.
Packaging dimensions	188 × 165 × 53 mm
Units per package	1
Materials	Aluminium / Polycarbonate





Fit 48V, is a spotlight for low voltage tracklight applications which is available in five sizes (ø50, ø35, ø35 double, ø20 and ø20 double). Cylindrical geometry and essential forms, it stands out for its minimalistic looking and its functionality as it can be orientated in any direction. The black perimeter around its mouth and its honeycomb accessory, highlights its anti-glare vocation.

POLAR DIAGRAM



CONICAL DIAGRAM







	PRODUCT
Model	Anti-glare Honeycomb Louver
Reference	A345-00-00
Category	Accessories

NOT SOLD SEPARATELY.



Accessory made up of louver in the shape of a honeycomb panel to reduce glare and the effects of direct rays of vision.

48V SYSTEM  
TRACK 48V




TRACK 48V TRIMLESS

TRACK 48V TRIMLESS 1m	A338-01-00-	N
TRACK 48V TRIMLESS 2m	A338-02-00-	N
TRACK 48V TRIMLESS 3m	A338-03-00-	N
TRACK 48V TRIMLESS Corner 90° One Plane	A338-06-00-	N
TRACK 48V TRIMLESS Corner 90° Two Planes	A338-07-00-	N

RECOMMENDED FOR INSTALLATIONS WHERE THE PROFILE CAN BE INSTALLED BEFORE THE FALSE PLASTERBOARD CEILING (THICKNESS 12,5mm.)




TRACK 48V TRIMLESS  
Corner 90° One Plane




\*Electrical connection not included

TRACK 48V TRIMLESS  
Corner 90° Two Planes



\*Electrical connection not included




TRACK 48V SURFACE


TRACK 48V SURFACE 1m	A338-11-00-	N
TRACK 48V SURFACE 2m	A338-12-00-	N
TRACK 48V SURFACE 3m	A338-13-00-	N
TRACK 48V SURFACE Corner 90° One Plane	A338-14-00-	N



TRACK 48V SURFACE  
Corner 90° One Plane



\*Electrical connection not included




		P	V	D
CONSTANT VOLTAGE LED POWER SUPPLY	0434-01-21	75W	48V	180 x 52 x 30mm
	0434-01-22	150W	48V	240 x 60 x 49mm

DROP VOLTAGE TABLE


POWER (W)	CABLE SECTION (mm <sup>2</sup> )	CABLE LENGTH (m)			
		5	10	20	30
75	0,75	50	50	30	X
	1,5	50	50	50	50
150	0,75	40	15	X	X
	1,5	50	40	20	X

48V SYSTEM  
TRACK 48V


ALL 48V TRACK




**TRACK 48V Live-End Connector**  
A338-00-01- | N |



**TRACK 48V Central Connector**  
A338-00-02- | N |



**TRACK 48V Corner 90° Connector**  
A338-00-12- | N |



**TRACK 48V Wireless Control**  
0434-01-31- | N | Casambi/AAG Stucchi App  
0434-01-32- | N | AAG Stucchi App

TRIMLESS 48V




**TRACK 48V TRIMLESS Short T-Bracket**  
A338-00-03



**TRACK 48V Clamp for M6 ROD**  
A338-00-09

\*See accessories quantities




**TRACK 48V TRIMLESS Long T-Bracket**  
A338-00-04



**TRACK 48V Track Clamp**  
A338-00-10

\*See accessories quantities




**TRACK 48V TRIMLESS Straight Joiners (2 units)**  
A338-00-05



**TRACK 48V TRIMLESS Suspension Kit**  
A338-00-08

\*See accessories quantities



**TRACK 48V TRIMLESS Plaster Installation Guard 1m**  
A338-00-21

**\* SUGGESTED MOUNTING ACCESSORIES QUANTITIES**  
1000mm - 2 Pcs.  
2000mm - 3 Pcs.  
3000mm - 4 Pcs.

COLOUR | N ■ |

48V SYSTEM  
TRACK 48V

TRIMLESS, SURFACE & SUSPENSION 48V




TRACK 48V TRIMLESS & SURFACE End  
A338-00-06- | N |




TRACK 48V TRIMLESS & SURFACE End Feed  
A338-00-07- | N |

SURFACE, SUSPENSION 48V



TRACK 48V SURFACE Straight Joiner  
A338-00-11- | N |


SURFACE 48V



TRACK 48V Power Supply Case  
A338-00-20- | N | NO DIM


\*To be installed aside 48V Surface Tracks  
Power supply not included

SUSPENSION 48V



TRACK 48V Wired Power Supply Case  
A338-00-22- | N | NO DIM  
A338-00-23- | N | DIM

\*Power supply not included



TRACK 48V SURFACE Suspension Kit (2 units)  
A338-00-15- | N |



TRACK 48V SURFACE Suspension Feed Kit  
A338-00-16- | N | NO DIM  
A338-00-17- | N | DIM

\*For remote power supply

COLOUR | N ■ |