




DIMENSIONS



ACCESSORIES



WIRE TRIMLESS ACCESSORY

	PRODUCT
Name	DRUM 70 SUSPENSION DIM 1/10V 4000K WT
Reference	A3581032WT
Color	Textured white
RAL	9016
Category	SUSPENSION
	LIGHTING INFORMATION
Light source	LED
Gross luminous flux	8175 Lm
Power	59,5 W
Power values of the system	66,11 W
Colour temperature	4000 K
Colour Rendering Index	CRI>90
Chromatic stability	MacAdam Step 2
Light beam angle	96°
Lighting efficiency	87%
Efficacy	137 Lm/W
Current intensity	700 mA
Dimming	1-10V
Control through bluetooth	Please Consult
Driver	Included
Electrical insulation class	
Voltage	220 V/240 V
Frequency	50/60 Hz
Energy efficiency	A+
LED lifespan	L80B10 (Tc=80°C) >60.000h
	OTHER DATA
Ingress Protection	IP20
Cord length	Max. 2 m
Fast adjustment tensioner	Yes
Weight	10500 g.
Packaged weight	11534,3 g.
Packaging dimensions	765 × 765 × 150 mm
Units per package	1
Materials	Aluminium / Polymethyl Methacrylate



AWARDS






01-07-21 / 13:10

A large seized ceiling luminaire offering a major luminous flux, either as surface or as suspended fitting, with the action of the surface of the surfacepossibility to hang it at any desired height. Drum is dimmable in order to be allowed to adapt the light volume at any time exactly to the specific needs of each application or situation. In terms of forms its design is expressed in a surrounding slightly curved circular strip. Counting with a perfect, homogeneous light diffusion and the attractive illusion of a natural skylight.






POLAR DIAGRAM



CONICAL DIAGRAM



UGR

Glare Evaluation According to UGR										
ρ Ceiling	70	70	50	50	30	70	70	50	50	30
ρ Walls	50	30	50	30	30	50	30	50	30	30
ρ Floor	20	20	20	20	20	20	20	20	20	20
Room Size X Y	Vie	Viewing direction at right angles to lamp axis			les	Viewing direction parallel to lamp axis				
2H 2H 3H 4H 6H 8H 12H	18.2 19.8 20.5 21.0 21.2 21.3	19.4 21.0 21.6 22.0 22.2 22.2	18.5 20.2 20.8 21.4 21.6 21.7	19.7 21.3 21.9 22.3 22.5 22.6	19.9 21.5 22.1 22.6 22.8 22.9	18.2 19.8 20.5 21.0 21.2 21.3	19.4 21.0 21.6 22.0 22.2 22.2	18.5 20.2 20.8 21.4 21.6 21.7	19.7 21.3 21.9 22.3 22.5 22.6	19.9 21.5 22.1 22.6 22.8 22.9
4H 2H 3H 4H 6H 8H 12H	18.7 20.6 21.4 22.1 22.3 22.5	19.8 21.5 22.2 22.8 23.0 23.1	19.0 21.0 21.8 22.5 22.8 22.9	20.1 21.9 22.6 23.2 23.4 23.5	20.3 22.2 23.0 23.6 23.8 23.9	18.7 20.6 21.4 22.1 22.3 22.5	19.8 21.5 22.2 22.8 23.0 23.1	19.0 21.0 21.8 22.5 22.8 22.9	20.1 21.9 22.6 23.2 23.4 23.5	20.3 22.2 23.0 23.6 23.8 23.9
8H 4H 6H 8H 12H	21.7 22.5 22.9 23.1	22.4 23.1 23.3 23.5	22.2 23.0 23.4 23.6	22.8 23.5 23.8 24.0	23.2 24.0 24.3 24.5	21.7 22.5 22.9 23.1	22.4 23.1 23.3 23.5	22.2 23.0 23.4 23.6	22.8 23.5 23.8 24.0	23.2 24.0 24.3 24.5
12H 4H 6H 8H	21.8 22.6 23.0	22.4 23.1 23.4	22.2 23.1 23.5	22.8 23.5 23.9	23.2 24.0 24.4	21.8 22.6 23.0	22.4 23.1 23.4	22.2 23.1 23.5	22.8 23.5 23.9	23.2 24.0 24.4
Variation of the observer position for the luminaire distances S										
S = 1.0H S = 1.5H S = 2.0H	+0.1 / -0.1 +0.2 / -0.4 +0.4 / -0.7			+0.1 / -0.1 +0.2 / -0.4 +0.4 / -0.7						
Standard table Correction Summand	Correction			BK06 -2.0						
Corrected Glare Indices referring to 8175lm Total Luminous Flux										






DRUM

FEED




	PRODUCT
Model	Mains Thick Trimless
Reference	A023-00-02- W N
Colour	W □ RAL 9016 N ■ RAL 9005
Category	Accessories



FASTENING



	PRODUCT
Model	Steel Cable Trimless
Reference	A023-00-05- W N
Colour	W □ RAL 9016 N ■ RAL 9005
Category	Accessories
	4 Pcs. needed



Wire Trimless Accessory is a collection of accessories for fitting tensioners and cables to Arkoslight luminaires suspended directly from the ceiling with any visible ceiling rose or fixings. This achieves a minimalist application with a visually tidy finish.

With Wire Trimless Accessory the items adjacent to the ceiling of the standard product (ceiling roses, fixings, driver boxes, etc.) are concealed by a simple recessed application.

Wire Trimless Accessory reduces the visual impact of the installation leading to extremely minimalist aesthetics. The wires come out of the ceiling material as a part of the structure. This detail creates a much purer, more essential layout, particular when several luminaires are fitted in an arrangement.

