


SIX L RECESSED 2 DIM PUSH 34° 4000K NT



DIMENSIONS



ACCESSORIES



HIGH CHROMATIC LED

11010101100	1.207.2222111			
Color	Textured black			
Power of the system	9016			
Category	CEILING RECESSED			
	LIGHTING INFORMATION			
Light source	LED			
Gross luminous flux	3000 Lm			
Power	24,5 W			
Power values of the system	26,92 W			
Colour temperature	4000 K			
Colour Rendering Index	CRI>90			
Chromatic stability	Mac Adam Step 2			
Light beam angle	34°			
Lighting efficiency	90%			
Efficacy	122 Lm/W			
Current intensity	700 mA			
Dimming	Push			
Control through bluetooth	Please Consult			
Driver	Included			
Emergency power supply	Please Consult			
Electrical insulation class				
Voltage	220 V/240 V			
Frequency	50/60 Hz			
Energy efficiency	A+			
LED lifespan	L80B10 (Tj=85°C) >60.000h			
	OTHER DATA			
Ingress Protection	IP20			
Recess measurements	Ø62 mm.			
Swivel angle	310°			

PRODUCT

A2872222NT

Name Reference



350°

745 g.

890 g.

222 × 195 × 91 mm.

Rotation angle Weight

Packaged weight

Units per package

Materials

Packaging dimensions



Aluminium / Polycarbonate

AWARDS






Six Recessed is a spotlight for single recessed lighting solutions that stands out for its elegance and airiness. Its body; disk looking, rounded shaped, encloses an innovative combination of reflector and lens. The combined action of both, allows Six to direct light rays with the maximum uniformity in a very small distance that, at the same time, has made possible its differential design-reduced and minimalist-. In addition, Six can be freely articulated due to its airy arm which allows the spotlight to be orientated in any direction.






POLAR DIAGRAM



CONICAL DIAGRAM



FOR COMMERCIAL PRODUCT SHOWCASING

Vivid Model Colour Temperature	2700K	3000K	3500K	4000K	Light Pink
Reading			•	•	
Fruits & Vegetables		•	•		
⊕ Bakery	•				
2 Retail		•	•		
Cosmetics			•	•	
Q; Meat					•
Fish				•	
Seafood				•	•



For some of its products, Arkoslight offers the possibility to provide them with a special LED, designed to create an illumination focused on visually promoting goods or products for commercial purposes. It is a high chromaticity LED, capable of identifying the colour shades that produce a positive psychological perception of the illuminated object.

This special LED lighting source offers a much more attractive and intense colour range than a conventional LED, besides being much wider. Technically, this is possible thanks to a special LED setting that includes a «special saturation parameter», capable of highlighting the objects colours and materials in such a way that they seem more attractive within the visible light spectrum. To achieve this performance, in each case, the appropriate diode and specific phosphor coating are carefully selected.

